

Tecplot RS 2024 Release 1

Tutorial

Tecplot, Inc. Bellevue, Washington December 2024 Copyright © 1988-2024, Tecplot, Inc. All rights reserved worldwide. Except for personal use, this manual may not be reproduced, transmitted, transcribed, stored in a retrieval system, or translated in any form, in whole or in part, without the express written permission of Tecplot, Inc., 3535 Factoria Blvd S.E. Suite 550, Bellevue, WA 98006, U.S.A.

This software and documentation are furnished under license for utilization and duplication only according to the license terms. Documentation is provided for information only. It is subject to change without notice. It should not be interpreted as a commitment by Tecplot, Inc. Tecplot assumes no liability or responsibility for documentation errors or inaccuracies.

SOFTWARE COPYRIGHTS

Tecplot RS, Tecplot © 1988-2024 Tecplot, Inc. All rights reserved worldwide.

ENCSA Hierarchical Data Format (HDF) Software Library and Utilities © 1988-1998 The Board of Trustees of the University of Illinois. All rights reserved. Contributors include National Center for Supercomputing Applications (NCSA) at the University of Illinois, Fortner Software (Windows and Mac), Unidata Program Center (netCDF), The Independent JPEG Group (JPEG), Jean-loup Gailly and Mark Adler (gzip). Bmptopnm, Netpbm © 1992 David W. Sanderson. Dlcompat © 2002 Jorge Acereda, additions and modifications by Peter O'Gorman. Ppmtopict © 1990 Ken Yap.

TRADEMARKS

Tecplot RS, Tecplot, Preplot, and Framer are registered trademarks or trademarks of Tecplot, Inc.

Encapsulated PostScript, FrameMaker, PageMaker, PostScript, Premier—Adobe Systems, Incorporated. Ghostscript—Aladdin Enterprises. Linotronic, Helvetica, Times—Allied Corporation. LaserWriter, Mac OS X—Apple Computers, Incorporated. AutoCAD, DXF—Autodesk, Incorporated. Chears—ChevronTexaco Corporation. Compaq Computer Corporation. Élan License Manager is a trademark of Élan Computer Group, Incorporated. Alpha, DEC, Digital, LaserJet, HP-GL, HP-GL/2, PaintJet—Hewlett-Packard Company. X-Designer— Imperial Software Technology. Builder Xcessory—Integrated Computer Solutions, Incorporated. IBM, RS6000, PC/DOS—International Business Machines Corporation. Bookman—ITC Corporation. VIP—Landmark Graphics Corporation. X Windows— Massachusetts Institute of Technology. MGI VideoWave—MGI Software Corporation. ActiveX, Excel, MS-DOS, Microsoft, Visual Basic, Visual C++, Visual J++, Visual Studio, Windows, Windows Metafile—Microsoft Corporation. HDF, NCSA—National Center for Supercomputing Applications. UNIX, OPEN LOOK—Novell, Incorporated. Motif—Open Software Foundation, Incorporated. Gridgen—Pointwise, Incorporated. Eclipse, FrontSim—Schlumberger, Limited. IRIS, IRIX, OpenGL—Silicon Graphics, Incorporated. Open Windows, Solaris, Sun, Sun Raster— Sun MicroSystems, Incorporated. All other product names mentioned herein are trademarks or registered trademarks of their respective owners.

NOTICE TO U.S. GOVERNMENT END-USERS

Use, duplication, or disclosure by the U.S. Government is subject to restrictions as set forth in subparagraphs (a) through (d) of the Commercial Computer-Restricted Rights clause at FAR 52.227-19 when applicable, or in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.227-7013, and/or in similar or successor clauses in the DOD or NASA FAR Supplement. Contractor/manufacturer is Tecplot, Inc., Post Office Box 3633, Bellevue, WA 98009-3633.

Contents

CONFIGURING YOUR SYSTEM1Plot Styles and Simulator Selection1RS_USER Environment Variable2MANUAL ORGANIZATION3THE TECPLOT RS ENVIRONMENT4The Plot Area4The Plot Area4The Dolbar6The Sidebar7Help7Welcome Screen8CHAPTER 1: BASIC XY PLOTS91.1 LOADING XY DATA FILES91.1 LOADING XY DATA FILES91.2 XY VARIABLES PLOT10Choosing Entities11Displaying Multiple Variables12Creating Multiple Variables14Stepping Through Entities151.3 XY ENTITIES PLOTS16Single Entity Plot16Multiple Entities17Sum and Average Options181.4 SAVING A PROJECT FILE19CHAPTER 2: XY PLOT APPERARNCE212.1 PAPER LAYOUT21Adding Your Company Name22Saving the Paper Layout Template232.2 CUSTOMIZATION USING PLOT OPTIONS242.3 SAVE CHANGES TO THE PROJECT FILE27	INTRODUCTION		1
Plot Styles and Simulator Selection 1 RS_USER Environment Variable 2 MANUAL ORGANIZATION 3 THE TECPLOT RS ENVIRONMENT 4 The Plot Area 4 The Plot Area 4 The Menu Bar 5 The Toolbar 6 The Sidebar 7 Help. 7 Welcome Screen 8 CHAPTER 1: BASIC XY PLOTS 9 1.1 LOADING XY DATA FILES 9 1.2 XY VARIABLES PLOT 10 Choosing Entities 11 Choosing Variables 11 Displaying Multiple Variables 12 Creating Multiple Variables 14 Save a Gallery Plot 16 Single Entity Plot 16 Multiple Entities PloTS 16 Single Entity Plot 17 Sum and Average Options 18 1.4 SAVING A PROJECT FILE 19 CHAPTER 2: XY PLOT APPEARANCE 21 2.1 PAPER LAYOUT 21 Adding Your Company Name 22 Saving the Paper Layout Template 23 <td>CO</td> <td>NFIGURING YOUR SYSTEM</td> <td>1</td>	CO	NFIGURING YOUR SYSTEM	1
RS_USER Environment Variable2MANUAL ORGANIZATION3THE TECPLOT RS ENVIRONMENT4The Plot Area4The Plot Area4The Menu Bar5The Toolbar6The Sidebar7Help7Welcome Screen8CHAPTER 1: BASIC XY PLOTS91.1 LOADING XY DATA FILES91.2 XY VARIABLES PLOT10Choosing Entities11Displaying Multiple Variables11Displaying Multiple Variables14Stepping Through Entities151.3 XY ENTITIES PLOTS16Single Entity Plot16Multiple Entities Plot17Sum and Average Options181.4 SAVING A PROJECT FILE19CHAPTER 2: XY PLOT APPEARANCE212.1 PAPER LAYOUT21Adding Your Company Name22Saving the Paper Layout Template232.2 CUSTOMIZATION USING PLOT OPTIONS242.3 SAVE CHANGES TO THE PROJECT FILE27		Plot Styles and Simulator Selection	1
MANUAL ORGANIZATION3THE TECPLOT RS ENVIRONMENT4The Plot Area4The Plot Area4The Plot Area4The Menu Bar5The Toolbar6The Sidebar7Help7Welcome Screen8CHAPTER 1: BASIC XY PLOTS91.1 LOADING XY DATA FILES91.2 XY VARIABLES PLOT10Choosing Entities11Displaying Multiple Variables12Creating Multiple Variables12Creating Multiple Y Axes14Save a Gallery Plot14Stepping Through Entities151.3 XY ENTITIES PLOTS16Single Entity Plot17Sum and Average Options181.4 SAVING A PROJECT FILE19CHAPTER 2: XY PLOT APPEARANCE212.1 PAPER LAYOUT21Adding Your Company Name22Saving the Paper Layout Template232.2 CUSTOMIZATION USING PLOT OPTIONS242.3 SAVE CHANGES TO THE PROJECT FILE27		RS_USER Environment Variable	2
THE TECPLOT RS ENVIRONMENT4The Plot Area4The Plot Area4The Nenu Bar5The Toolbar6The Sidebar7Help7Help.7Welcome Screen8CHAPTER 1: BASIC XY PLOTS91.1 LOADING XY DATA FILES91.2 XY VARIABLES PLOT10Choosing Entities11Displaying Multiple Variables12Creating Multiple Variables12Creating Multiple Y Axes14Save a Gallery Plot14Stepping Through Entities151.3 XY ENTITIES PLOTS16Single Entity Plot17Sum and Average Options181.4 SAVING A PROJECT FILE19CHAPTER 2: XY PLOT APPEARANCE212.1 PAPER LAYOUT21Adding Your Company Name22Saving the Paper Layout Template232.2 CUSTOMIZATION USING PLOT OPTIONS242.3 SAVE CHANGES TO THE PROJECT FILE27	MA	NUAL ORGANIZATION	3
The Plot Area4The Menu Bar5The Toolbar6The Sidebar7Help7Welcome Screen8CHAPTER 1: BASIC XY PLOTS91.1 LOADING XY DATA FILES91.2 XY VARIABLES PLOT10Choosing Entities11Choosing Entities11Displaying Multiple Variables12Creating Multiple Y Axes14Save a Gallery Plot151.3 XY ENTITIES PLOTS16Single Entity Plot16Multiple Entities Plot17Sum and Average Options181.4 SAVING A PROJECT FILE19CHAPTER 2: XY PLOT APPEARANCE212.1 PAPER LAYOUT21Adding Your Company Name22Saving the Paper Layout Template232.2 CUSTOMIZATION USING PLOT OPTIONS242.3 SAVE CHANGES TO THE PROJECT FILE27	TH	E TECPLOT RS ENVIRONMENT	4
The Menu Bar5The Toolbar6The Sidebar7Help7Welcome Screen8CHAPTER 1: BASIC XY PLOTS91.1 LOADING XY DATA FILES91.2 XY VARIABLES PLOT10Choosing Entities11Choosing Entities11Displaying Multiple Variables12Creating Multiple Y Axes14Save a Gallery Plot151.3 XY ENTITIES PLOTS16Single Entity Plot16Multiple Entities Plot17Sum and Average Options181.4 SAVING A PROJECT FILE19CHAPTER 2: XY PLOT APPEARANCE212.1 PAPER LAYOUT21Adding Your Company Name22Saving the Paper Layout Template232.2 CUSTOMIZATION USING PLOT OPTIONS242.3 SAVE CHANGES TO THE PROJECT FILE27		The Plot Area	4
The Toolbar6The Sidebar7Help7Welcome Screen8CHAPTER 1: BASIC XY PLOTS91.1 LOADING XY DATA FILES91.2 XY VARIABLES PLOT10Choosing Entities11Choosing Variables11Displaying Multiple Variables12Creating Multiple Y Axes14Save a Gallery Plot14Stepping Through Entities151.3 XY ENTITIES PLOTS16Single Entity Plot16Multiple Entities Plot17Sum and Average Options181.4 SAVING A PROJECT FILE19CHAPTER 2: XY PLOT APPEARANCE212.1 PAPER LAYOUT21Adding Your Company Name22Saving the Paper Layout Template232.2 CUSTOMIZATION USING PLOT OPTIONS242.3 SAVE CHANGES TO THE PROJECT FILE27		The Menu Bar	5
The Sidebar7Help7Welcome Screen8CHAPTER 1: BASIC XY PLOTS91.1 LOADING XY DATA FILES91.2 XY VARIABLES PLOT10Choosing Entities11Displaying Multiple Variables12Creating Multiple Variables12Creating Multiple Y Axes14Save a Gallery Plot14Stepping Through Entities151.3 XY ENTITIES PLOTS16Single Entity Plot16Multiple Entities Plot17Sum and Average Options181.4 SAVING A PROJECT FILE19CHAPTER 2: XY PLOT APPEARANCE212.1 PAPER LAYOUT21Adding Your Company Name22Saving the Paper Layout Template232.2 CUSTOMIZATION USING PLOT OPTIONS242.3 SAVE CHANGES TO THE PROJECT FILE27		The Toolbar	6
Help.7Welcome Screen8CHAPTER 1: BASIC XY PLOTS91.1 LOADING XY DATA FILES91.2 XY VARIABLES PLOT10Choosing Entities11Displaying Multiple Variables11Displaying Multiple Variables12Creating Multiple Y Axes14Save a Gallery Plot14Stepping Through Entities151.3 XY ENTITIES PLOTS16Single Entity Plot16Multiple Entities Plot17Sum and Average Options181.4 SAVING A PROJECT FILE19CHAPTER 2: XY PLOT APPEARANCE212.1 PAPER LAYOUT21Adding Your Company Name22Saving the Paper Layout Template232.2 CUSTOMIZATION USING PLOT OPTIONS242.3 SAVE CHANGES TO THE PROJECT FILE27		The Sidebar	7
Welcome Screen8CHAPTER 1: BASIC XY PLOTS91.1 LOADING XY DATA FILES91.2 XY VARIABLES PLOT10Choosing Entities11Choosing Variables11Displaying Multiple Variables12Creating Multiple Y Axes14Save a Gallery Plot14Stepping Through Entities151.3 XY ENTITIES PLOTS16Single Entity Plot16Multiple Entities Plot17Sum and Average Options181.4 SAVING A PROJECT FILE19CHAPTER 2: XY PLOT APPEARANCE212.1 PAPER LAYOUT21Adding Your Company Name22Saving the Paper Layout Template232.2 CUSTOMIZATION USING PLOT OPTIONS242.3 SAVE CHANGES TO THE PROJECT FILE27		Help	7
CHAPTER 1: BASIC XY PLOTS91.1 LOADING XY DATA FILES91.2 XY VARIABLES PLOT10Choosing Entities11Choosing Variables11Displaying Multiple Variables12Creating Multiple Y Axes14Save a Gallery Plot14Stepping Through Entities151.3 XY ENTITIES PLOTS16Single Entity Plot16Multiple Entities Plot17Sum and Average Options181.4 SAVING A PROJECT FILE19CHAPTER 2: XY PLOT APPEARANCE21Adding Your Company Name22Saving the Paper Layout Template232.2 CUSTOMIZATION USING PLOT OPTIONS242.3 SAVE CHANGES TO THE PROJECT FILE27		Welcome Screen	8
1.1 LOADING XY DATA FILES91.2 XY VARIABLES PLOT10Choosing Entities11Choosing Wariables11Displaying Multiple Variables12Creating Multiple Y Axes14Save a Gallery Plot14Stepping Through Entities151.3 XY ENTITIES PLOTS16Single Entity Plot16Multiple Entities Plot17Sum and Average Options181.4 SAVING A PROJECT FILE19CHAPTER 2: XY PLOT APPEARANCE212.1 PAPER LAYOUT21Adding Your Company Name22Saving the Paper Layout Template232.2 CUSTOMIZATION USING PLOT OPTIONS242.3 SAVE CHANGES TO THE PROJECT FILE27	CHAPTER 1: BASI	C XY PLOTS	9
1.2 XY VARIABLES PLOT.10Choosing Entities11Choosing Variables11Displaying Multiple Variables12Creating Multiple Y Axes14Save a Gallery Plot.14Stepping Through Entities151.3 XY ENTITIES PLOTS16Single Entity Plot.16Multiple Entities Plot17Sum and Average Options181.4 SAVING A PROJECT FILE19CHAPTER 2: XY PLOT APPEARANCE.212.1 PAPER LAYOUT21Adding Your Company Name22Saving the Paper Layout Template232.2 CUSTOMIZATION USING PLOT OPTIONS242.3 SAVE CHANGES TO THE PROJECT FILE27	1.1	LOADING XY DATA FILES	9
Choosing Entities11Choosing Variables11Displaying Multiple Variables12Creating Multiple Y Axes14Save a Gallery Plot14Stepping Through Entities151.3 XY ENTITIES PLOTS16Single Entity Plot16Multiple Entities Plot17Sum and Average Options181.4 SAVING A PROJECT FILE19CHAPTER 2: XY PLOT APPEARANCE212.1 PAPER LAYOUT21Adding Your Company Name22Saving the Paper Layout Template232.2 CUSTOMIZATION USING PLOT OPTIONS242.3 SAVE CHANGES TO THE PROJECT FILE27	1.2	XY VARIABLES PLOT	0
Choosing Variables11Displaying Multiple Variables12Creating Multiple Y Axes14Save a Gallery Plot14Stepping Through Entities151.3 XY ENTITIES PLOTS16Single Entity Plot16Multiple Entities Plot17Sum and Average Options181.4 SAVING A PROJECT FILE19CHAPTER 2: XY PLOT APPEARANCE212.1 PAPER LAYOUT21Adding Your Company Name22Saving the Paper Layout Template232.2 CUSTOMIZATION USING PLOT OPTIONS242.3 SAVE CHANGES TO THE PROJECT FILE27		Choosing Entities1	1
Displaying Multiple Variables12Creating Multiple Y Axes14Save a Gallery Plot14Stepping Through Entities151.3 XY ENTITIES PLOTS16Single Entity Plot16Multiple Entities Plot17Sum and Average Options181.4 SAVING A PROJECT FILE19CHAPTER 2: XY PLOT APPEARANCE212.1 PAPER LAYOUT21Adding Your Company Name22Saving the Paper Layout Template232.2 CUSTOMIZATION USING PLOT OPTIONS242.3 SAVE CHANGES TO THE PROJECT FILE27		Choosing Variables1	1
Creating Multiple Y Axes14Save a Gallery Plot14Stepping Through Entities151.3 XY ENTITIES PLOTS16Single Entity Plot16Multiple Entities Plot17Sum and Average Options181.4 SAVING A PROJECT FILE19CHAPTER 2: XY PLOT APPEARANCE212.1 PAPER LAYOUT21Adding Your Company Name22Saving the Paper Layout Template232.2 CUSTOMIZATION USING PLOT OPTIONS242.3 SAVE CHANGES TO THE PROJECT FILE27		Displaying Multiple Variables1	2
Save a Gallery Plot14Stepping Through Entities151.3 XY ENTITIES PLOTS16Single Entity Plot16Multiple Entities Plot17Sum and Average Options181.4 SAVING A PROJECT FILE19CHAPTER 2: XY PLOT APPEARANCE212.1 PAPER LAYOUT21Adding Your Company Name22Saving the Paper Layout Template232.2 CUSTOMIZATION USING PLOT OPTIONS242.3 SAVE CHANGES TO THE PROJECT FILE27		Creating Multiple Y Axes1	4
Stepping Through Entities151.3 XY ENTITIES PLOTS16Single Entity Plot16Multiple Entities Plot17Sum and Average Options181.4 SAVING A PROJECT FILE19CHAPTER 2: XY PLOT APPEARANCE212.1 PAPER LAYOUT21Adding Your Company Name22Saving the Paper Layout Template232.2 CUSTOMIZATION USING PLOT OPTIONS242.3 SAVE CHANGES TO THE PROJECT FILE27		Save a Gallery Plot 1	4
1.3 XY ENTITIES PLOTS16Single Entity Plot16Multiple Entities Plot17Sum and Average Options181.4 SAVING A PROJECT FILE19CHAPTER 2: XY PLOT APPEARANCE212.1 PAPER LAYOUT21Adding Your Company Name22Saving the Paper Layout Template232.2 CUSTOMIZATION USING PLOT OPTIONS242.3 SAVE CHANGES TO THE PROJECT FILE27		Stepping Through Entities1	5
Single Entity Plot16Multiple Entities Plot17Sum and Average Options181.4 SAVING A PROJECT FILE19CHAPTER 2: XY PLOT APPEARANCE212.1 PAPER LAYOUT21Adding Your Company Name22Saving the Paper Layout Template232.2 CUSTOMIZATION USING PLOT OPTIONS242.3 SAVE CHANGES TO THE PROJECT FILE27	1.3	XY ENTITIES PLOTS	6
Multiple Entities Plot17Sum and Average Options181.4 SAVING A PROJECT FILE19CHAPTER 2: XY PLOT APPEARANCE212.1 PAPER LAYOUT21Adding Your Company Name22Saving the Paper Layout Template232.2 CUSTOMIZATION USING PLOT OPTIONS242.3 SAVE CHANGES TO THE PROJECT FILE27		Single Entity Plot1	6
Sum and Average Options181.4 SAVING A PROJECT FILE19CHAPTER 2: XY PLOT APPEARANCE212.1 PAPER LAYOUT21Adding Your Company Name22Saving the Paper Layout Template232.2 CUSTOMIZATION USING PLOT OPTIONS242.3 SAVE CHANGES TO THE PROJECT FILE27		Multiple Entities Plot	7
1.4 SAVING A PROJECT FILE19CHAPTER 2: XY PLOT APPEARANCE212.1 PAPER LAYOUT21Adding Your Company Name22Saving the Paper Layout Template232.2 CUSTOMIZATION USING PLOT OPTIONS242.3 SAVE CHANGES TO THE PROJECT FILE27		Sum and Average Options1	8
CHAPTER 2: XY PLOT APPEARANCE.212.1 PAPER LAYOUT21Adding Your Company Name22Saving the Paper Layout Template232.2 CUSTOMIZATION USING PLOT OPTIONS242.3 SAVE CHANGES TO THE PROJECT FILE27	1.4	SAVING A PROJECT FILE	9
 2.1 PAPER LAYOUT	CHAPTER 2: XY PL	OT APPEARANCE	1
Adding Your Company Name22Saving the Paper Layout Template232.2CUSTOMIZATION USING PLOT OPTIONS242.3SAVE CHANGES TO THE PROJECT FILE27	2.1	PAPER LAYOUT 2	1
Saving the Paper Layout Template		Adding Your Company Name 2	2
2.2 CUSTOMIZATION USING PLOT OPTIONS		Saving the Paper Layout Template2	3
2.3 SAVE CHANGES TO THE PROJECT FILE	2.2	CUSTOMIZATION USING PLOT OPTIONS	4
	2.3	SAVE CHANGES TO THE PROJECT FILE 2	7

CHAPTER 3: MULT	II-FRAME XY PLOTS	29
3.1	THE MULTI-FRAME OPTIONS DIALOG	29
3.2	MULT-FRAME IN XY ENTITIES	31
3.3	MULTI-FRAME PAPER LAYOUT	32
	Save Gallery Plot #2	35
3.4	SAVE CHANGES TO THE PROJECT FILE	36
CHAPTER 4: FILTE	RS	37
4.1	THE NEED FOR FILTERS	37
4.2	THE TYPE FILTER	38
4.3	THE ENTITY FILTER	39
4.4	SORTING	41
4.5	SELECTION METHODS	41
CHAPTER 5: SELEC	CTION SETS	43
5.1	CREATING SELECTION SETS	43
	Selecting by Entity Name	44
	Selecting by Variable Value	44
5.2	VIEWING AND EDITING SELECTION SETS	45
5.3	USING SELECTION SETS	46
5.4	SAVE CHANGES TO THE PROJECT FILE	47
CHAPTER 6: USER	GROUPS	48
6.1	PREPARATION	48
6.2	CREATION	49
6.3	SAVE THE PROJECT FILE CHANGES	50
CHAPTER 7: XY EC	QUATIONS	51
7.1	WRITING EQUATIONS	52
7.2	SAVING AND LOADING EQUATIONS	53
7.3	APPLYING EQUATIONS	53
7.4	PROJECT FILE CHANGES	54
CHAPTER 8: CUST	OM PLOTS	55
8.1	THE CUSTOM OPTIONS DIALOG	55
8.2	CREATING XY CUSTOM PLOTS	57
	The Play Button	61
8.3	SAVE PROJECT FILE CHANGES	61

CHAPTER 9: COMPARING XY DATA SETS	
9.1 LOADING MULTIPLE DATA FILES	
The Active Data Set	
9.2 COMPARING DATA SETS WITHIN A FRAME	
Altering Styles for Comparison Data Sets	
The Delta Option	
9.3 WHAT CAN BE COMPARED ?	
9.4 COMPARING DATA SETS IN XY FREESTYLE.	
CHAPTER 10: RFT PLOTS	
10.1 LOADING RFT DATA	
10.2 RFT PLOTS	
Save Gallery Plot #3	
10.3 COMPARING RFT PLOTS	
CHAPTER 11: COMPLETION PROFILES	
Save Gallery Plot #4	
CHAPTER 12: PLOT GALLERY	
CHAPTER 13: FLOW TABLES	
13.1 LOADING FLOW TABLE DATA	
13.2 THE FLOW TABLES SELECTIONS	
Flow Table Number	
Multi	
Single	
CHAPTER 14: SETTING AXIS RANGES AND SCALES	
14.1 FRAME RANGE	
14.2 DATA RANGE	
14.3 MANUAL RANGE	
14.4 AXIS SCALES	
14.5 LOG SCALES	
14.6 SAVING PLOT STYLES IN A NAMED FILE	

CHAPTER 15:	LOADING GRID DATA	
	15.1 LOAD GRID DIALOG	
	Grid File Types	
	15.2 GRID LOADING OPTIONS	100
	Grid Optimization	101
	Tolerances	103
	The RSGRID file	103
	15.3 LOADING THE GRID	104
	15.4 LOADING MULTIPLE GRID FILES	105
	The Manage Data dialog	105
	15.5 SAVE A PROJECT FILE	106
		107
CHAPIER 16:		
	16.1 SELECTING THE GRID PLOT TYPE	
	16.2 GRID SIDEBARS	
	16.3 CHANGING THE VIEW (ROTATE, TRANSLATE, AND 200M)	
	Zooming In/Out	
	Panning	
	Adjusting the 3D View	
	Rotating the 3D View	112
	Reset View	112
	View Presets	112
	Paper Zoom	112
	16.4 SELECTING VARIABLES	113
	16.5 SELECTING TIMES	114
	Stepping Through Times	114
	Animating the Time Sequence	114
	Controlling Animation Speed	115
	16.6 VARIABLE DISPLAY TOGGLES	116
	OWG (Oil / Water / Gas) Saturation Plots	116
	The Delta Toggle	117
	K Sum and K Avg (3D plots only)	118
	16.7 SELECTING 2D PLANES	118

16.8 WELLS TOGGLE	120
Using Zone Layers and Zone Effects to View the Grid Interior	122
Changing Well Styles	122
More Wells	125
Save Your Project File	128
16.9 MORE OPTIONS	128
HAPTER 17: MULTI-FRAME GRID PLOTS	129
17.1 THE MULTI-FRAME OPTIONS DIALOG	129
17.2 DISPLAYING MULTIPLE GRID VIEWS	130
17.3 CHANGING VARIABLES IN MULTI-FRAME VIEWS	131
17.4 FRAME LINKING	131
Link Grid View / Rotation	131
Link Layer Toggles	132
Link Well Toggle	133
Link Inside Views / Blanking	133
17.5 SPECIAL PURPOSE MULTI-FRAME PLOTS	133
Dual Porosity Views	133
Side-By-Side Grid Comparisons	134
HAPTER 18: ADVANCED GRID PLOTS	135
18.1 QUICK 3D	137
18.2 LGRs	139
18.3 INSIDE VIEWS	141
IJK Slices	141
XYZ Slices	143
Arbitrary Slices	144
Additional Inside Views	147
18.4 GRID DATA EQUATIONS	148
18.5 VALUE BLANKING	151
Value Blanking in Multi-Frame Plots	153
18.6 DATA INTEGRATION	154
18.7 QUICK PLOTS	156
Histograms	156
Time/history Cell Plots	158

CHAPTER 19: COMBO PLOTS	161
19.1 TIME/HISTORY WELL PLOTS	161
19.2 BUBBLE PLOTS	162
19.3 STREAMLINES	164
Time Slider	166
Select By	167
Color By	167
Skip	167
Time of Flight	168
Use Log Scale	168
CHAPTER 20: GRID COMPARISON PLOTS	169
In Conclusion	175

INTRODUCTION

Welcome to Tecplot RS! We're very happy to include you among our many delighted customers. The manual you are reading outlines important information you need to get the most out of your new program so that you can quickly produce detailed and high-quality plots of your reservoir data.

This document is intended as a tutorial to get you up and running with RS as quickly as possible. Most of what you need to know to create plots for viewing reservoir data is contained within this manual. Your installation also contains a comprehensive User Manual that goes into more detail. You will occasionally be directed to that document for a deeper explanation of certain features. We encourage you to use both documents to learn all the functionality that is available to you.

CONFIGURING YOUR SYSTEM

Before using Tecplot RS for the very first time, there are a couple of settings that you can make that will greatly enhance your experience. If Tecplot RS is running, you should close it before making these changes.

Plot Styles and Simulator Selection

RS can read data files from a variety of simulators, and you are not limited to using just one. However, if you identify the type of files that you most frequently use, RS can pre-set some defaults that will create better plots 'out of the box'.

RS will apply styles such as line colors and patterns according to the property being shown. It does this using a lookup table of property (variable) name and the associated styles. Since property names are generally specific to the simulator, if you identify the simulator then your initial list of property names will be appropriate. If you use multiple simulators, the other property names and associated styles can be easily added to the table. This setting just gives you a starting point.

In the root folder of your Tecplot RS installation (for Windows platforms this is usually C:\Program Files\Tecplot\TecRS 2024 R1) you will see several files with names such as

rsvariables_eclipse.txt and rsvariables_cmg.txt. These files contain simulator-specific data that provide the starting point for creating tables of styles to be used when creating plots in RS.

On your *very first* launch of the RS program, you'll get a small dialog that prompts you for the style definitions to use. Since the example data files for this tutorial are in Eclipse format, you should choose the Eclipse/SLB option. You should also check the toggle to "Set as Default", as it will ensure that this option is always used by default.

If this dialog does NOT appear, it means that a default has already been established. No problem! From the menu select Options > Plot Options and then access the Variables tab. If the Eclipse/SLB option is not shown as the version being used, simply click on the [Change...] button and this same dialog will be launched, allowing you to change it.

🚺 RSVariables 🛛 👔 💌
Simulator variable set
Eclipse/SLB
CHEARS
VIP/Nexus
CMG Samea (TETRAD
Sensor/TETRAD
Select the simulator that best defines the variable naming conventions for the files that you will be using. Note that this does NOT limit the file types that can be loaded.
Set as <u>D</u> efault
OK Help

RS_USER Environment Variable

After your first time using RS, you should notice that it remembers your previous settings and will default to those options when possible. These include such things as plot styles, the most recent files loaded, and the display state (e.g. the type of plot and the property being displayed) when you last used a particular data file. The defaults are saved in small files that, in most cases, you aren't even aware of and can be deleted with no harm.

It is sometimes desirable for these defaults to be shared by everyone using the program, or you may prefer to save these settings on a per-user basis. The RS_USER environment variable is a way to have more control over this. When RS_USER is set, it defines a folder that controls the *first* place RS will look for the files that are used to record the defaults. Each user can specify their own location, thus ensuring that Bill's preferences do not interfere with Mary's.

The environment variable setting is optional. When used, you will know exactly where your preferences are being recorded and this will reduce the likelihood of interfering with others who have different preferences. Simply choose a writable folder where these files should be placed and create an environment variable named RS_USER that points to that folder. The **Help About Tecplot RS** dialog will display the RS_USER environment variable setting.

MANUAL ORGANIZATION

This document is organized into 2 parts. Part I (chapters 1–13) covers XY Plots, or the line plots typically used to display observed or simulated data for individual wells or other entities. Part II (chapters 14–19) contains instructions for Grid Plots; 2D and 3D plots of the entire reservoir, with the ability to animate the display to see changes in variable values over time.

The chapters in each part are organized much like a training seminar might be. They start by introducing basic operations in the early chapters and then continue into the more advanced functions in subsequent sections. Most concepts are presented as a series of exercises that you may work along with if you like. The data files used in the examples were installed along with the software. Installation of Tecplot RS is usually quite simple and automatic, and instructions for doing so are presented in a separate document.

GOOD IDEA

Even if you have a need for only the grid plotting functions, you should read and do the examples in Chapters 1 through 5. These chapters explain some basic concepts that are used in both XY and Grid plots.

THE TECPLOT RS ENVIRONMENT

When you launch the program your screen should look something like this:



The Plot Area

The largest part of the work environment is the plot area. This is where the images you create will be displayed. You'll see a white area that represents the page on which plots would be printed.

Each page may contain one or more **frames**. The frame acts as the container for all drawing elements. Each frame can be independently sized and positioned on the paper. Because most items in a plot are scaled relative to the frame, you can create layouts that will automatically adjust to different paper sizes, or resize frames to squeeze in an extra image at the last minute.



The very first time you use Tecplot RS, the sidebar may appear much wider than shown here. To fix this, use the mouse to 'grab' the right edge of the sidebar and drag it all the way to the left. This will reset it, and the setting should be 'remembered' in subsequent uses of the program..

The Menu Bar

C Tecplot RS Project Edit View Plot Type Templates Gallery Data Options Insert Plot Frame Analyze Macro Help

The Menu Bar gives you access to the various functions within Tecplot RS.

- Project Loading, saving, and exporting data or images.
- Edit Standard copy/cut/paste operations
- View Control the look of the workspace and the view of the data
- Plot Type Switch between the many different types of plots in RS
- Templates Create, save, and apply custom views that you define.
- Gallery Save finished plots and come back to them at any time.
- Data Display data info and alter the data via equations or other means.
- Options Customize how Tecplot RS works for you.
- Insert Add text, geometries, and images to your plots.
- Plot Miscellaneous settings that control the appearance of certain plots.
- Frame Create new frames and order or arrange existing ones.
- Analyze Create plots with analysis data such as histograms.
- Macro Record and play back scripts to automate repetitive tasks.
- Help Access the documentation and help for RS.

6

The Toolbar

🗋 📄 🔐 📆 📆 💭 🔍 🔶 🗳 🌽 🏹 🏹 🗩 🕟 🍆 🚣 📰 🖓 🖓 🖓 🖓 🖓 🍪

Buttons on the toolbar give you one click access to many of the functions found in the menu bar. You can hover over the buttons to display a tool tip that describes the operation. There are 29 buttons organized in 6 groups by category. From left to right they are:

• File handling group

- o Create new project
- Open existing project
- Load XY data
- $\circ \quad \text{Load grid data} \\$
- View group
 - Zoom in/out
 - Move plot (pan)
 - Rotate around the Z-axis
 - Roller-ball rotation

• Plot control group

- Mouse select mode
- Adjust mode
- Add/edit text
- o Plot options
- Query group
 - o Measure mode
 - o Probe mode
 - o Quick probe
- Display data group
 - Add streamtraces
 - $\circ \quad \text{Cell blanking} \\$
- Analysis
 - o Histogram plots
 - o Cross plots
 - o Integration

- o Load VDB data
- o Manage data
- Save project
- o Move light source
- o Redraw
- o Reset to default view
- o Multi-Frame options
- Update the paper layout template

- Create new variables with equations
- o Macros

The Sidebar

Although pop-up dialogs are used for some operations, most of your inputs and selections will be made in the sidebar area. The sidebar will change according to the Plot Type (XY Variables, 2D Grid, 3D Grid, etc.) you have selected.

You can completely turn off the sidebar, which will give you the maximum plot area. You can also detach the sidebar from the main window. To do this, double-click on the top portion of the sidebar frame where it reads "Plot Controls". You can then drag the sidebar to a new location. To re-dock the sidebar, double-click again on that same area.

While most controls on the sidebar change according to the plot type, there are several that are common to more than one.

Mesh
Contour
Connect
Shade
🔲 Light
Translucency

The toggles on the sidebar are primarily used to turn on and off the various drawing layers or elements of the plot. For example, when displaying 2D or 3D Grids you can control whether or not the mesh is shown, or whether to draw the wells. Note that you may elect to have the toggles applied on a frame-by-frame basis (giving you the ability to turn off the mesh on one

frame and have it on in a second), or have them applied to all frames in a multi-frame plot. This selection is made in the Multi-Frame dialog.

The current plot type is displayed in a small option menu at the bottom of the sidebar. This simply duplicates the Plot Type options on the menu bar, and you can make a selection in either place.

2D Grid	▼]	?
---------	-----	---

Help

In addition to the manuals, on-line help is available throughout the program. The small ? button next to the control shown above will bring up help for the current plot type. Help buttons are also included on individual dialogs that bring up context-sensitive assistance for the problem at hand. Finally, you can also navigate through the entire collection of help screens from the **Help > Tecplot RS Help** option from the main menu.

Welcome Screen

Every time you start Tecplot RS, the Welcome Screen will appear:



In this window you'll see a list of your most recent projects, which can be quickly loaded by simply clicking on the file name. You'll also have links to the documentation included in the installation, online resources, menu options for loading new files, version information, and notifications about new releases of the software that may be downloaded. Some of these features duplicate options in the main menu and toolbar, but this screen is designed to present the most frequently needed first steps for working with Tecplot RS. The window will automatically close once you load a file or project, or you may close it using the [X] in the top right corner.

CHAPTER 1: BASIC XY PLOTS

1.1 LOADING XY DATA FILES

Your first step will be to load a file containing the data you wish to plot. Tecplot RS supports a variety of file types from a number of sources, including output from several popular simulators plus user-created files containing observed data. Appendix F contains detailed information about supported file types.

Click on 📴 from the toolbar, or select	💟 Load XY Data 🛛 💌
Project > Load XY Data from the menu. This will bring up the dialog shown here:	Elle type: Individual files
The File name(s) list shows what has been selected so far (nothing yet).	Enable reload (unsmry files only) Create history data set Auto-append secondary (RFT and WAF) files Load derived vars (when available)

Start by clicking on the **Add...** button to choose the data file for this first exercise. This will bring up a typical file browser dialog such as this one:

Open Files	Brown Files & Techlet & Tech 20m	Pr. L. ovamalor, L	4 Search ave	malar	×
Organize •	New folder	ix recamples r	Jearch exa	85 - 1	. 0
☆ Favorites	Name	Date modified	Туре	Size	
	comparisons	7/11/2016 1:13 PM	File folder		
🥽 Libraries	Completions	7/11/2016 1:13 PM	File folder		
	퉬 streamlines	7/11/2016 1:13 PM	File folder		
📜 Computer	chelan.frft	7/8/2016 1:03 AM	FRFT File	158	KB
	chelan.hist	7/8/2016 1:03 AM	HIST File	70	KB
👊 Network	chelan.unsmry	/2016 1:03 AM	UNSMRY File	127	KB
	quinaultlgr-xyp.unsmry	7/8/2016 1:03 AM	UNSMRY File	60	KB
	File name: chelan.unsmry		- Eclipse(SLB)	/Chears files (*.	J*S* ▼
			<u>O</u> pen	Can	cel

We'll start with an Eclipse Unified Summary file (UNSMRY), so change the file filter to reflect that option. Then navigate to the examples folder, which will be in the location where Tecplot RS was installed. On Windows installations, this is usually C:\ Program Files\Tecplot\TecRS 2024 R1\ examples. Finally, select the Chelan.unsmry file and click Open.

When you get back to the Load XY Data dialog, you'll see the Chelan.unsmry file in the list of file names. Click on the **OK** button to load the data.

1.2 XY VARIABLES PLOT

The program should display the XY Variables plot type. This happens automatically when the first file opened is an XY file. However, if you previously selected a different option, it may be necessary for you to choose the correct plot type now. Do this by selecting **Plot Type** > XY Variables from the menu or sidebar.

Using the lists in the sidebar, select OIL-01 in Entities and WPR in the Y1 variables list.



Congratulations! You've just created your first plot with Tecplot RS.

Choosing Entities

Near the top of the sidebar is a list of all the entities found in the sample file. From this list you can choose the structure or data that will be plotted. Right now, the first entity in the list (OIL-01) is highlighted and displayed.

You should now select a different entity. There are several ways to do this:

- Use the mouse to click on a different name, such as OIL-03.
- Click on the [>] (next) or [<] (previous) buttons beneath the list.
- If the control containing the list is active (has focus), then the up and down arrow keys on your keyboard may be used.

Note how each time you choose a different entity, the plot changes instantly.

Choosing Variables

Beneath the entity list are three controls containing a list of all variables found in the file. With these options you have complete control over which values are shown and on which axes. By default, the program puts time or date on the X-axis and the first variable other than time or date on the first Y-axis.

You should now choose a different variable for the Y1 axis. For example, choose FIELD from the Entity list box and GPR from the Y1 axis variable list box, your display should then look like this.

As with entity selections, note how the plot is updated instantly when you choose a new variable.



Displaying Multiple Variables

Although the entity list allows you to select only a single well, you may choose to display multiple variables in your plot. To start, highlight both OPR and GPR in the Y1 axis list box. This plot should instantly change to show two lines for the selected entity; a green one representing the oil production rates, and a red one for the gas production rates.

DID YOU KNOW ?	 Normally, when you choose one item in a list box the highlight on the previously selected item is cleared. To make multiple selections in a list box that allows them, you can use the following techniques: To choose two or more consecutive items, you can click on the first one and then, while holding down the left mouse button, "drag" the highlight to the last item before releasing the mouse button. You can also choose a range of items by clicking on the first one and then holding down the [Shift] key while clicking on the last item. To choose two or more non-consecutive items, hold down the [Ctrl] key and click on the desired selections.
?	 click on the desired selections. [Ctrl] + click can also be used to un-select a single item without removing your other selections. [Ctrl] and the drag or [Shift] + click method may be used together to choose consecutive items without undoing previous selections.

Since you chose both OPR and GPR in the Y1 axis list box, both variables are scaled to a single Y axis on the left side of the plot. Since both values have similar value ranges (even though the units are different), the plot is acceptable.



Now add WPR to currently selected Y1 axis variables ([Ctrl] + click) to display a total of three variables. For the FIELD entity, your plot would look something like this:



Since the production rates for oil and gas are an order of magnitude greater than the water rates (not to mention different units), we don't see much variation in the WPR line.

Creating Multiple Y Axes

To solve this problem, let's move the water production rate to a second Y axis. To do this, simply click on WPR in the second list box.



A second Y axis has been created and automatically scaled to ranges more suitable for the water production rate.

Save a Gallery Plot

It's time to save your first Gallery Plot. You'll learn more about these in a later chapter, but for now just follow these steps:

1. From the menu bar, select **Gallery > Save**.

2. A small dialog will pop up asking for a name. Enter **Field Production Rates**. As you work through the examples you'll be asked to save additional gallery plots. Be sure to do these steps AND those that have you save a Project File, which is covered in section 1.4.

You can have a total of up to 5 Y-axes, and you can choose multiple variables for each. The variable selections for the additional axes are made in the same list box that was used for the second Y axes.

Use the small drop list labeled "Y2-5" to control which axis you are selecting variables for.

Y1:		Y2-5:	2	•	$\langle \square$	This selection tells RS which axis you
GPR	•	SWP			,	are choosing a
LGC		VIC				variable for.
LGR		VIR				
OIC		VPC				
OIR	_	VPR				
ONLINE		WCT				
OPC	=	WHP				
OPR		WIC				
STS		WIR				
SWP		WOR		=		
VIC		WPC				
VIR	_	WPR				
VDC	T			-		

Stepping Through Entities

Once you have chosen the desired variables and the axes on which you would like them to be displayed, try stepping through the various entities. One option is to click on the "Next" button: IP This will display each entity in turn.

You can also automate the entire sequence of entities. Start by selecting the first entity in the list, and then press the "Play" button:

Chapter 1: Basic XY Plots

1.3 XY ENTITIES PLOTS

There are other types of XY plots, but the methods used to create them are essentially the same as what you've already learned. Let's look at another type by selecting **Plot Type > XY Entities** from the menu.

Single Entity Plot

At first glance it may appear that this is no different from the XY Variables plots that you just made. The difference is that with XY Variables, the plot shows a single entity with one or more variables. But with XY Entities, the plot displays a single variable for one or more entities.

The default selections are highlighted, and you should see a simple plot for the Water Production Rate for the OIL-01 well. (If not, make these selections as shown to the right.) Now the Previous and Next buttons will cycle through the variables and update the plot accordingly.

Plot Controls	₽ ×
V Lines	Filter
V Symbols	Reload
Variables	
X: DATE	•
Y: SWP VIC VIR VPC VPR WCT WHP WIC WIR WOR WPC WPR	
41 ib bb 🖩	R.
Entities	+
OIL-01 OIL-02 OIL-03 OIL-04 GAS-05 FIELD	
Data Set	
Compare	Options
XY Entities	▼ ?

Multiple Entities Plot

To see the real difference between the XY Entities and XY Variables plot types, select multiple items from the Entities list. Highlight OIL-01 through OIL-04, and you should immediately see a plot that looks similar to the following:



With XY Entities plots, you can compare the same variable for multiple wells or other entities. You can now look at different variables for all four wells by stepping through the variable selections. You can also press the Play button to automatically scroll through all variables.

Sum and Average Options

Now click on the Sum toggle to turn it on:



And instantly see the resulting plot...



With just a click of a toggle, you have instructed Tecplot RS to add the values for two or more wells (those selected in the Entities list). There's also a toggle to average values.

1.4 SAVING A PROJECT FILE

As your final step in this exercise, you're going to create a **Project File.** On the menu, choose **Project > Exit**.

A dialog will pop up asking if you want to save your current project. Choose YES.

Enter "Chelan" as the name of the project and click the Save button.

Project files are one of the greatest time savers available in Tecplot RS. A project file saves the names of all the files you have loaded, the styles (plot appearance) that you have defined, and the plot type and selections active at the time the project was saved. The purpose is to return you to the same place (or nearly so) the next time you use those files.

With the project file, you can now interrupt your work in the Quick Start tutorial and return to it later without having to repeat previous steps.

When you restart Tecplot RS, your ten most recent project files are listed in the Project menu and/or the Welcome Screen, so a single click is all that is needed to select one. As you do additional work, you will be asked if you want to save any changes to the project file. Changes might include loading additional data files, refining styles, etc. For this tutorial, always save those changes unless you have specific reasons not to.

CHAPTER 2: XY PLOT APPEARANCE

Now that you have a general idea about how to create a plot, let's look at changing it to match the way **you** want it to look. If necessary, start RS and choose the Chelan project file (created in the previous chapter) from the list of files under the **Project** drop-down menu.

2.1 PAPER LAYOUT

The plots you created in Chapter 1 had titles, a legend, and date information. These reflected the factory defaults for a **paper template** that is used for all plots in RS. You don't have to use these defaults – the Paper Layout function lets you create new templates to your specifications. You can even tell RS to use a specific template every time you run the program.

Choose **Plot Type > Paper Layout**. Your plot will disappear, and the sidebar will change to reflect the options for Paper Layout.

While in Paper Layout mode, you can modify or create new templates for all your plots. You can add text, titles, legends, and other standard items. You'll have complete control over the font, color, size, and placement of each item.

The RS templates are stored in files that you can name and load as needed, so you can create many different styles for use with different types of plots. To help get you started, a couple of sample template files were included and installed along with Tecplot RS.

Complete information about the Paper Layout templates can be found in Appendix B of the User's Manual. For now, you'll just make use of some pre-defined templates.

Paper	Paper	lot Controls						ð
✓ Show Paper Size: Color: Letter ✓ White Dimensions: Orientation: Height: 8.5 Width: 11.0 Frames Plot: Header: Footer: ✓ Show Style ✓ Show B H: 5 W: 100 Style Style Dynamic Text RS_FILENAME RS_FILENAME RS_PLOTITILE RS_ENTITY RS_AVAILABLE RS_NNCVAR RS_NVALVAR RS_STREAMVAR RS_STREAMVAR RS STREAMVAR RS_DAGENNIM Add Text Title Options Page # 13 File Factory defaults Load Save As	✓ Show Paper Size: Color: Letter ✓ White Dimensions: Orientation: Height: 8.5 Width: 11.0 Frames Plot: Header: Footer: ✓ Show Style ✓ Show Y: 100 Style Style Dynamic Text RS_FRAMETITLE Style RS_PLOTITILE Style RS_PLOTITILE Style RS_NNCVAR RS_NVARABLE RS_NUVAR RS_STREAMVAR RS_DAGENUIM Madd Text Title Options Page # 13 Fie Factory defaults Load Save Save Save As	Paper			_			
Size: Color: Letter White Dimensions: Orientation: Height: 8.5 Width: 11.0 Frames Plot: Header: Footer: Style Show Show H: 8 H: 5 W: 100 W: 100 Style Style Dynamic Text RS_FILENAME RS_STREAMVAR RS_SNCVAR RS_STREAMVAR RS_STR	Size: Color: Letter V White Dimensions: Height: 8.5 Width: 11.0 Landscape V Frames Plot: Header: Footer: Style V Show V Show H: 8 H: 5 W: 100 W: 100 Style Style Dynamic Text RS_FILENAME RS_FAMETITLE RS_PLOTITLE RS_ENTITY RS_VARIABLE RS_NNCVAR RS_STREAMVAR RS_STREAMVAR RS_DAGENIIM Add Text Title Options Page # 13 File Factory defaults Load Save Save As Paper Layout V	Show Paper	r					
Letter White Dimensions: Height: 8.5 Width: 11.0 Frames Plot: Header: Footer: Style Style Style Style Dynamic Text RS_FILENAME RS_FRAMETITLE RS_FRAMETITLE RS_ENTITY RS_VARIABLE RS_NCVAR RS_STREAMVAR RS_STREAMVAR RS_DAGENIIM Add Text Title Options Page # 13 File Factory defaults Load Save Save As	Letter White Umensions: Height: 8.5 Width: 11.0 Frames Plot: Header: Footer: Style Style Style Style Dynamic Text RS_FILENAME RS_FRAMETITLE RS_FRAMETITLE RS_POOTTITLE RS_POOTTITLE RS_NCVAR RS_STREAMVAR RS_STREAMVAR RS_DAGENIIM Add Text Title Options Page # 13 File Factory defaults Load Save Save As Paper Layout	Size:	Color					
Dimensions: Orientation: Height: 8.5 Width: 11.0 Frames Plot: Header: Footer: Style Show Show H: 8 H: 5 W: 100 W: 100 Style Style Dynamic Text RS_FILENAME RS_FRAMETITLE RS_FRAMETITLE RS_POTITLE RS_POTITLE RS_NCVAR RS_STREAMVAR RS_STREAMVAR RS_STREAMVAR RS_DAGFNIM Add Text Title Options Page # 13 File Factory defaults Load Save Save As	Dimensions: Height: 8.5 Width: 11.0 Frames Plot: Header: Footer: Style Show Show H: 8 H: 5 W: 100 W: 100 Style Style Dynamic Text RS_FILENAME RS_FRAMETITLE RS_FILENAME RS_FRAMETITLE RS_FILENAME RS_FARAMETITLE RS_STREAMVAR RS_STREA	Letter 🔹				White		
Width: 11.0 Landscape	Width: 11.0 Landscape	Dimensions: Height: 8.5	Orier	ntation:				
Frames Plot: Header: Footer: Style Show Show H: 8 H: 5 W: 100 W: 100 Style Style Dynamic Text RS_FILENAME RS_FALMETITLE RS_ENTITY RS_VARIABLE RS_NNCVAR RS_STREAMVAR RS_STREAMVAR RS_STREAMVAR RS_DAGENIIM Add Text Title Options Page # 13 File Factory defaults Load Save Save As	Frames Plot: Header: Footer: Style Show Show H: 8 H: 5 W: 100 W: 100 Style Style Dynamic Text RS_FILENAME RS_FALMETITLE RS_ENTITY RS_VARIABLE RS_NNCVAR RS_STREAMVAR RS_STREAMVAR RS_STREAMVAR RS_DAGENHIM Add Text Title Options Page # 13 File Factory defaults Load Save Save As Paper Layout	Width: 11.0	Land	dscape				•
Plot: Header: Footer: Style Show Show H: 8 H: 5 W: 100 W: 100 Style Style Dynamic Text RS_FILENAME RS_FILENAME RS_FAMETITLE RS_ENTITY RS_VATIABLE RS_INCVAR RS_STREAMVAR RS_STREAMVAR RS_STREAMVAR RS_DAGENIIM Add Text Title Options Page # 13 File Factory defaults Load Save Save As	Plot: Header: Footer: Style Show Show H: 8 H: 5 W: 100 W: 100 Style Style Style Dynamic Text RS_FILENAME A RS_FILENAME RS_FAMETITLE RS_ENTITY RS_ENTITY RS_NNCVAR RS_STREAMVAR RS_STREAMVAR RS_STREAMVAR N File File File Factory defaults Load Save Save As Paper Layout It if	Frames						
Style Show Show H: 8 H: W: 100 W: Style Style Dynamic Text RS_FILENAME RS_FAMETITLE RS_FAMETITLE RS_ENTITY RS_NNCVAR RS_STREAMVAR RS_OLGENTIM Add Text Title Options Page # Load Save	Style Show Show H: 8 H: 5 W: 100 W: 100 Style Style Dynamic Text RS_FILENAME RS_FALMETITLE RS_PILTITLE RS_ENTITY RS_VARIABLE RS_NNCVAR RS_STREAMVAR RS_STREAMVAR RS_DAGENIIM Add Text Title Options Page # 13 File Factory defaults Load at startup Load Save Save As	Plot:	Hea	der:		Foo	ter:	
H: 8 H: 5 W: 100 W: 100 Style Style Style Dynamic Text RS_FILENAME # RS_FALENAME # # RS_FAMETITLE # # RS_PLOTITILE # # RS_ENTITY # # RS_NNCVAR # # RS_OPTIMIM # # Add Text # # Title Options Page # 13 File # # Load at startup Load _ Save Save As *	H: 8 H: 5 W: 100 W: 100 Style Style Dynamic Text RS_FILENAME RS_FRAMETITLE RS_PLOTITLE RS_ENTITY RS_VARIABLE RS_NNCVAR RS_STREAMVAR RS_NCVAR RS_DAGENIIM Add Text Title Options Page # 13 File Factory defaults Load at startup Load Save Save As	Style] 🔽	Show		V	Show	
W: 100 W: 100 Style Style Style Dynamic Text RS_FILENAME / RS_FRAMETITLE # / RS_PLOTITILE # RS_NCVAR RS_NCVAR RS_STREAMVAR RS_STREAMVAR Title Options Page # Title Options Page # Load at startup Load Save Save As	W: 100 W: 100 Style Style Style Dynamic Text RS_FILENAME # RS_FRAMETITLE # # RS_PLOTITLE # RS_NCVAR RS_NCVAR RS_STREAMVAR # Title Options Page # Itile Options Page # Itile Options Save Save Save As		H:	8		H:	5	
Style Style Style Style Dynamic Text RS_FILENAME RS_FRAMETITLE # RS_FRAMETITLE # RS_POTITITE # RS_NNCVAR RS_NNCVAR RS_STREAMVAR # Title Options Page # Title Options Page # Itadat startup Load Save Save As	Style Style Style Style Dynamic Text RS_FILENAME RS_FRAMETITLE RS_FARMETITLE RS_PLOTITILE RS_ENTITY RS_NNCVAR RS_NNCVAR RS_STREAMVAR RS_STREAMVAR Title Options Page # 13 File File Factory defaults Load Save Save As		w:	100		w:	100	
Style Style Dynamic Text RS_FILENAME RS_FRAMETITLE RS_PCATITLE RS_PCATITLE RS_NCVAR RS_STREAMVAR RS_STREAMVAR RS_DAGENIIM Add Text Title Options Page # 13 File Factory defaults Load at startup Load Save Save As	Style Style Dynamic Text RS_FILENAME RS_FRAMETITLE RS_PCTITLE RS_PCTITLE RS_NNCVAR RS_STREAMVAR RS_STREAMVAR RS_DAGENIIM Add Text Title Options Page # 13 File Factory defaults Load at startup Load Save Save Save As Paper Layout		_					
Dynamic Text RS FILENAME RS_FRAMETITLE RS_PCATITLE RS_PLOTITLE RS_NNCVAR RS_STREAMVAR RS_DAGENIIM Add Text Title Options Page # 13 File Factory defaults Load at startup Load Save Save As	Dynamic Text RS FILENAME RS_FRAMETITLE RS_PCATITLE RS_PLOTITLE RS_NNCVAR RS_STREAMVAR RS_DAGENIIM Add Text Title Options Page # 13 File Factory defaults Load at startup Load Save Save As Paper Layout			Style			Style	
RS_FILENAME RS_FRAMETITLE RS_PLOTITILE RS_ENTITY RS_VARABLE RS_NNCVAR RS_STREAMVAR RS_DAGENIIM Add Text Title Options Page # 13 File Factory defaults Load at startup Load Save Save As	RS_FILENAME RS_FRAMETITLE RS_PLOTITILE RS_ENTITY RS_VARABLE RS_NNCVAR RS_STREAMVAR RS_DAGENIIM Add Text Title Options Page # 13 File Factory defaults Load at startup Load Save Save As Paper Layout	Dynamic Text -						
Add Text Title Options Page # 13 File Factory defaults Load at startup Load Save Save As	Add Text Title Options Page # 13 File Factory defaults Load at startup Load Save Save As Paper Layout	RS_FRAMETIT RS_PLOTTITLI RS_ENTITY RS_VARIABLE RS_NNCVAR RS_STREAMV RS_STREAMVI RS_DAGENIUM						-
Title Options Page # 13 File Factory defaults Load at startup Load Save Save As	Title Options Page # 13 File File Factory defaults Load at startup Load Save Save Save As Paper Layout Image: Contemport	Add Text	J					
File Factory defaults Load at startup Save Save Save Save As	File Factory defaults Load at startup Load Save Save Save As Paper Layout	Title Options	Pag	e # 1	3			
Factory defaults Coad at startup Load Save Save Save Save As	Factory defaults Load at startup Load Save Save As Paper Layout	File						
Load at startup Load Save Save Save As	Load at startup Load Save Save As Paper Layout	Factory default	s					
Load Save Save As	Load Save Save As	Load at sta	rtup					
Save Save As	Save Save As	Load						
Save Save As	Paper Layout		_					
	Paper Layout 🗸 🔽	Save				Save	AS	_

From the Paper Layout sidebar press the **Load...** button. This will bring up a separate file loading dialog. The sample files are in the **examples** folder under your Tecplot home directory (the one you selected when you first installed Tecplot RS). Find and load the file named "SingleFrame.rslayx".

Once loaded, your display should look similar to this:



Adding Your Company Name

The sample template contains a place for your company name, indicated with an arrow above. You're going to make a quick change to the template to insert the correct name.

Double-click the text that reads "YOUR COMPANY NAME." The Text Details dialog appears:

💟 Text Details 🛛 💌
YOUR COMPANY NAME
Helvetica Bold Size 2.2 Frame%
Color Black Line Spacing 1
Angle (deg) 0 🔹 Text Box
Position By Frame Anchor
Close Cancel Help

Change the text so that the correct name appears in the text box, then press the **Close** button. The display will be updated with the name you selected.

Saving the Paper Layout Template

Click on the **Save As** button. Assign a new name for the file, such as "MyTemplate1". You can also toggle on the option to "Load at startup". If you do so, the next time you run Tecplot RS, it will automatically use this layout for your plot.

From the menu, choose **Plot Type > XY Variables** or **Plot Type > XY Entities** to return to your previous plot. Your plot should reappear, but it will now use the modified template including your company name.

2.2 CUSTOMIZATION USING PLOT OPTIONS

There are many more ways of fine-tuning the appearance of your plots. This exercise will introduce Plot Options. Start by creating an XY plot using XY Variables. Make sure you're using XY Variables and not XY Entities, and that OPR is one of the variables being shown. It doesn't matter which entity (well) you choose.

Now double-click on the green line representing OPR. This should launch the Plot Options dialog, and OPR should be highlighted in the selection list:

Load / Save Variables	XV Lines	VV Avec	Cride	Crid Logand	Crid Avec	Coll Labela	Welle
Load / Save Valiables	AT LINES	AT Axes	Grius	Ghu Legenu	GHU AXES	Cell Labels	Weils
Style set: Active	•	Lines					
<u>V</u> ariable:	÷	<u>C</u> olor	Defa	ult		•	
GPR		<u>P</u> attern	Defa	ult		•	
LGC LGR		Length	1%			•	
MWPR	_	Thickness	0.40				
OIC			0.40				
OPC	=	Symbols					_
OPR		Colo <u>r</u>	Matc	h Line		•	V Fill
ST2		S <u>h</u> ape	Defa	ult		•	
ST3		Spacing	D = 4	1%		•	
ST4 ST5		Size	1.00				
ST6	-	0120	1.00				
Long names							
Apply						Multi-Edit S	tyles
					(Help

This page shows the styles that are used when plotting OPR (Oil Production Rate) for the "Active" style set. Note that many of the options are shown as Default. This refers to the default styles that are defined by the Eclipse/SLB simulator option that you selected at the start of this tutorial.

If you wanted to change the defaults you could do so using the Variables tab. However, the default may also be referenced in style sets for comparison plots (these will be covered in a later chapter). For this exercise, you are going to change your plot's styles directly as opposed to redefining the "default" settings.

Using the controls on the dialog, change the line thickness to 0.7, and uncheck the Symbols toggle. Then press the Apply button to see the results, which should be a thicker line without symbols.

Next, use the sidebar to turn on GPR (if it's not already displayed). To alter the styles for this line, you can either double-click on the red line representing the gas production rate, or simply select it from the variable list in the Plot Options dialog.

Note that symbols are still turned on for this selection, and the line thickness remains at 0.4. Each variable (property) has its own set of styles. This makes it easier to differentiate them on a plot.

For the GPR, use the drop-down list for the symbol shape to select Character (at the bottom of the list). This will activate a small text field next to the list, and you should put the letter 'G' in that box. Change the symbol size to 1.8, and the line thickness to 0.1. Finally, press the Apply button.



The result is a greater distinction between styles for each line.

This exercise is intended as a basic introduction to Plot Options. In later chapters you'll be making more advanced changes. A complete discussion of Plot Options can be found in Appendix D of the RS User's Manual.

2.3 SAVE CHANGES TO THE PROJECT FILE

When asked if you want to save changes to the Chelan project file, be sure to do so. This will save the new paper layout template and changes to the line styles in Plot Options.

Note that you will get this message whenever you close the program or load a new project file, even if you've made no changes to the project. It's just a way to ensure that you never lose a setting that you wanted to keep.
CHAPTER 3: MULTI-FRAME XY PLOTS

Up to now, all the examples have utilized a single frame. In this exercise you will learn how to create a page containing multiple plots.

3.1 THE MULTI-FRAME OPTIONS DIALOG

With the Chelan data file loaded, go to the XY Variables plot type. If necessary, highlight the first entity in the list (OIL-01) and set up the variables so that OPR and GPR are on the Y1 axis, and WPR is on Y2.

To bring up the dialog that controls the multiframe options, you can either click on the multiframes button or choose **Options > Multi-Frame Options** from the menu. This will bring up the dialog shown here.

Change the Frame Mode to **Multi-Frame**. Make sure the other settings are also as shown, then click on **Close**.

🚺 Multi-Fr	ame Options	×		
Frame Mode	e:			
Single F	rame 💿 <u>M</u> ulti Frame			
Multi-Fran	nes			
<u>C</u> olumns	2	<u>*</u>		
<u>R</u> ows	2	*		
🔽 Link G	rid View / Rotation			
📃 Link <u>I</u> r	nside Views / Blanking			
🔽 Link L	ayer Toggles			
Link Well Toggle				
Frame Spacing				
2	% of Paper Size			
0.25	Mi <u>n</u> imum (Inches))		
Quick Plot	ts			
Location	<u>A</u> rea (%)			
Bottom of Page 30 Some state Some				
Right Side of Page				
Close	Apply Hel	lp 📃		



Your plot should immediately change to look something like this:

You should have a total of four frames (two rows by two columns), showing the first four wells.

Now click on the Next button low under the entity list. You'll notice that the highlighted entity "jumps" down four spaces and Gas-05 and the FIELD entities are displayed on your screen. The Next and Previous buttons automatically adjust to the number of frames selected for display.

Note that each frame displays the same set of variables and a different entity.

3.2 MULT-FRAME IN XY ENTITIES

Using the Plot Type menu, switch to XY Entities. Select the WIR variable and the FIELD entity. Make sure to turn off the Sum toggle if it's still on. Now you should have four frames for the FIELD entity, each showing a different variable:



Again, try the Next and Previous button controls. This time, they cycle through the variable selections. Not all variables are present or interesting for the FIELD entity, so some of these plots might be blank or display a message indicating that the variable does not exist. You might look at the other entities when you run into such a plot.

3.3 MULTI-FRAME PAPER LAYOUT

Now that we are displaying multiple frames, there is redundant information being displayed. The company name, file name, and date are repeated in each frame. In the XY Entities plots, the entity names are repeated, and in the XY Variables plots the same variable list appears in each frame. In this exercise, you'll instruct the system to use a paper layout template that cleans up the display.

From the menu, choose **Plot Type > Paper Layout**. Then click the **Load** button. As you did in the exercise in Chapter 2, you're going to use a sample layout that was provided with your software. This one is named "MultiFrame.rslayx", and it is also in the **examples** folder under the Tecplot RS home directory.

Once loaded, your template should look something like this:

RS_PLOTTITLE
RS_FRAMETITLE
R6_O RENTXX00
RS_STREAMVAR
RS_NNCVAR
RS_BUBBLELEFEND

Don't worry that the template shows only a single frame even though you will be making multi-frame plots. The style in the single plot frame will be applied to all frames.

The new template differs from the previous one in that it makes use of the header and footer frames. The header and/or footer will appear only once on the paper. No plots will be placed in the header or footer – they can contain only text. Since the header and footer appear only once on the paper, they are the ideal place to put text that doesn't change from frame to frame.

Another advantage of the header and footer frames is that the text in it can never interfere with the plot itself.

In this sample paper template, the plot title has been placed in the header frame and the frame title in the plot frame. When creating plots, Tecplot RS will use the plot title for labels that apply to all frames of a multi-frame plot, and will use the frame title for items that change in each frame.

As in the first exercise, there is a place for your company name, this time in the footer frame. Double click on the text and change it accordingly. Finally, click on **Save As** and save your new template under a different name that you choose.

Return to the XY Variables plot type.

Your plot should now look something like this:



Note how the plot title (in the header) reflects the variable names, which are the same for all frames. Within each frame, the entity is identified in the space designated for the frame title.



Now switch to the XY Entities plot type and change the variable to GO1:

This time, the title in the header frame reflects the entity name (which is the same for every frame), and the titles in the individual frames identify the variables.

Save Gallery Plot #2

Save another gallery plot using **Gallery > Save**. The name will default to the one you saved before, but change it to **Field Multi Frames**. You have now saved two different plots to the gallery. You'll soon see how these are used.

3.4 SAVE CHANGES TO THE PROJECT FILE

As the final step in this exercise, save your changes to the project file, either by clicking on

the Save icon Government of the toolbar or selecting **Project > Save** from the menu. The project file will now contain your changes for the line styles, your paper layout template for the multi-frame plot, and the gallery plots.

CHAPTER 4: FILTERS

Assuming you are continuing from the previous exercise, you have the sample data file Chelan.unsmry loaded and the paper is set up for 4 frames (2 rows x 2 columns). With those settings in place, select the XY Entities plot type.

4.1 THE NEED FOR FILTERS

In the previous exercise, we saw that some variables do not exist for every entity. This leads to some plots in our multi-frame layout having only an error message in them, as shown below, where we have chosen the OIL-01 entity along with API as the Y variable.



Flip through the variables using the Previous and Next buttons.

Now choose FIELD as the entity and flip through the variables again using the Previous and Next buttons. Again, some frames will have the message, this time for different variables.

What is happening here is this: Entities are classified into different types. Type classifications include Field, Wells, Layers (completions), Groups, and other options that are simulator dependent. All entities of a single type share the same list of variables, but some variables will exist for one entity type but not another. For example, in this file the Field and Well types both include WPR, OPR, and GPR, but the VPR variable is used only for the Field, and the LGR variable is assigned only to Wells.

By default, the list shown in the dialog contains all variables, regardless of whether they are used in just one entity type or all of them. The entity list also contains all entities regardless of type. As you step through the variable list creating XY Entity plots, you will get the blank frames when one of the variables doesn't exist for the particular entity being plotted.

The filter option can solve this problem. When you click on the **Filter...** button, this dialog appears.

Entity Type Sorting So	Entity Type Sorting Wells Completions Field Groups/Areas Regions Flow Gather Stations Quality/Target RFT Data Blocks Segments (IIIE) Entity List Oil-01 Oil-02 Oil-02 Oil-04 GAS-05 FIELD Apply Apply Apply Apply	Filtering	
Entity List OIL-01 OIL-02 OIL-02 OIL-03 OIL-04 GAS-05 FIELD FIELD Add to selections Remove from selections Remove from selections Replace se	Entity List Name Values Sel Sets Oll-01 Oll-02 Oll-03 Oll-04 GAS-05 FTELD Search Condition Containing Add to selections Remove from selections Replace selections Apply	Entity Type Completions Field Groups/Areas Flow Gather Stations Quality/Target RFT Data Aquifers Blocks Segments	Sorting By Type By Entity Name By Variable Value Ascending Descending Variable TIME
Containing Image: Conta	FIELD Containing Q Add to selections Remove from selections Replace selections Apply Apply	 ▼ ■ ● Entity List OIL-01 OIL-02 OIL-03 OIL-04 GAS-05 	Apply Name Values Sel Sets Comparison String Search Condition
	Apply	FIELD	Containing Containing Remove from selections Replace selections

4.2 THE TYPE FILTER

There are two list boxes in the Filtering dialog. The top one contains the Entity Type list. This is a list of all the possible entity types. Note that some entity types may not be familiar to you. This is because the list includes the types used by all the different simulators that are supported by Tecplot RS, and some of the types may not apply to the simulator software that you are using. By choosing items in the filter list, you can limit both the variables and entities that are displayed in the main dialog. For example, if you choose "Wells" as the filter, only well entities will be shown in the entities list, and only those variables recorded for wells will be included in the variables list.

By default, all entity types except completions and blocks are selected, which is why Tecplot RS tried to plot variables that might not have existed for a particular entity.

The lower list box, titled "Entity List", contains a preview of the entities from the current data file that are of the type(s) selected in the Type Filter. If you choose Wells in the type filter, the lower list box will show you which of your entities belong to that classification.

In the Chelan data set, when you highlight only the Flow option in the upper list box, your lower list box is empty. This is an indication that the current file does not contain any entities of this type.

By choosing each type in succession, you can see exactly which entities (if any) belong to a classification. This information is also summarized on the Manage Data dialog.

You may select multiple types in the Filter list (Hint: use [Ctrl] + click to choose nonconsecutive items.) For this exercise, however, choose only the Wells option and then click on **OK**.

When you return to the XY Entities sidebar you'll notice that both the entity and variable lists are smaller. Now when you step through the different variables using the Next and Previous buttons, there will be no more blank frames.

4.3 THE ENTITY FILTER

Now let's return to the XY Variables plot type. Your type filter will still be set to display only the entities and variables in the Wells classification, and you can now use the Next and Previous buttons to scroll through the various wells.

What if you were interested in only some of these wells? For very large oil fields, the list can be quite long, and often you'll work with a subset of the available wells.

Entity List OIL-01 OIL-02 OIL-03 OIL-04 GAS-05	 This is where the Entity List becomes useful. Cli to return to the Filtering dialog. You will notice entities in the lower list box are selected. Change this by highlighting only a subset of thes exercise, choose wells 1, 3, and 4 (using [Ctrl] + and then click the OK button to return to your particular to the selected of the selected of the selected. 	ck on the Filter that, by default, a se entities. For th click to select 3 a plot.	button all the is nd 4)
	Now the only items that appear in the Entities list and on the plot are the three wells you selected in the Entity List.	Plot Controls	Filter Reload
Select All			
JUST A NOTE	After accessing the Filtering options, it may be necessary to reset the variables you would like to display. Because the application of a filter may change the variables available in the list, the selections are returned to the default state.		E.

After resetting the variables to be displayed, your plot should now be limited to only the three wells that interest you.

4.4 SORTING

There are additional options in the Filter dialog that further increase its power. The next one we'll examine is the Sorting option.

Return to the Filter dialog. In the Sorting section, choose "By Variable Value" and Descending order. You'll see that the Variable option menu becomes active. From this list, choose "WPR" (Water Production Rate), and press the **Apply** button.

Now your selection list is sorted so that the wells with the highest WPR appear first, and others follow in decreasing order.

	Entity List
Sorting	GAS-05
	OIL-02
By Type	OIL-01
By Entity Name	OIL-03 OIL-04
By Variable Value	
Ascending	
Descending	
Variable WPR 🔻	
Apply	

When sorting by variable values, Tecplot RS considers the maximum value for the variable over all time steps.

Note also that sorting the list does not change either the type filter or selections you made within the entity list. (For example, FIELD is not shown in the Entity List because we still have only Wells selected in the Entity Type list.) However, sorting *will* affect the order of the entities that appear on the sidebar, and also the order that they are plotted when you step through multiple plots or use the Play button. This is a great way of organizing your plots according to critical quantities.

4.5 SELECTION METHODS

Just as you can sort by various criteria, you can also automatically *select* entities using similar operations. For example, you can find all wells with names that begin with or contain a specified character or string of characters. You can choose wells according to production values that are above, below, or even between a set of limits that you specify.

You can even limit the search to a certain time range. So, for example, you can instruct the program to find all wells with Oil Production Rates that were above 500 STB/Day between 1966 and 1980.

These options are a way to automatically highlight items in the Selection List, so that you don't have to do so manually. In addition, you can specify whether the new entities are added to, removed from, or completely replace the current selections. This gives you a tremendous amount of flexibility and power to choose precisely the wells or other entities that interest you most.

Name	Values	Sel Sets		
Comparis	son String			
Search C	Condition			
Contain	ing		-	
Add to selections				
Remove from selections				
Replace selections				
Apply				

These automated selections are made using the tabs in the lower right corner of the Filters dialog.

Use the Name tab to designate criteria for finding wells by name, and the Values tab to do the search described above based on Oil Production Rate and Date.

After setting the selection criteria, press the **Apply** button to make the selections and see the changes highlighted in the Selection List.

Before using the Sel Sets tab, you'll need to know more about another powerful tool: **Selection Sets!**

CHAPTER 5: SELECTION SETS

Our example data set is small, but in the real world you could be dealing with projects containing thousands of wells. In those cases, choosing or making changes to the entities you want to include can be time consuming. The Filter dialog allows you to choose a subset of wells or other entities that are of interest to you. Those selections are then used in lists and other displays, making it much easier to find the entities you want.

It would be nice if those selections could be remembered for future use, and that's exactly what Selection Sets are all about!



At its simplest level, a selection set is simply a list

of entity names. Tecplot RS can save this list so that you can reload it, eliminating the need to repeat the selection process.

5.1 CREATING SELECTION SETS

Although there are other ways to create selection sets, the Filter dialog is a good place to start.

If you were following the examples in the preceding chapter, you have the Filter dialog displayed and wells OIL-01, 03, and 04 are highlighted in the selection list. You'll also see a button labeled "Make New SS", and a text field with "SS001" in it.

Press the Make button now. The only thing that will appear to happen is the text field will change to "SS002". However, you've just saved a selection set containing the items that were highlighted.

Selecting by Entity Name

From the Name tab, enter an 'L' in the text box labeled Comparison String. Make sure the Search Condition is set to Containing, and choose the radio button to Replace Selections.

When you press the Apply button, the items in the list box should change so that entities names containing an 'L' are highlighted (everything except GAS-05). Replace the "SS002" with "L Names" and again press **Make New SS**.

Name	Values	Sel Sets		
Comparis	son String			
L				
Search C	ondition			
Containi	ing		•	
O Add	to selection	IS		
C Remo	ove from se	elections		
Repla	ace selectio	ins		
Apply				
Make New SS				
make New	SS LINA	mes		

Name	Values Sel Sets	
Var V	/PR 🔻	
Is L	ess than 🔻	
Value 2	28 -	
Search	n Limits	
Al	From	
🔘 Da	ates To	
© Tir	mes	
Add to selections		
Remove from selections		
Replace selections		
Apply		
Make Nev	v SS Low H2O	

Selecting by Variable Value

Change to the Values tab, and fill out the options as shown here. Click on **Apply**, followed by **Make New SS**.

You now have three selection sets. SS001 contains the wells that you highlighted manually, "L Names" includes all entities with names containing the letter 'L', and "Low H2O' contains entities whose maximum water output is less than 28 BBL/Day.

5.2 VIEWING AND EDITING SELECTION SETS

Click on the **Edit SS...** button to bring up another dialog that will allow you to both view and alter your selection sets (NOTE: This dialog can also be accessed from the menu **Data > Selection Sets...**):

Selection Sets	X		
Selection Sets	Entities		
SS001 L Names	GAS-05 -00		
Low H2O			
Low H2O			
Rename			
Delete	Remove Items		
Load Imported sets will replace current ones.			
Sa <u>v</u> e			
OK Help			

When you highlight a selection set in the list on the left, the Entities list will update to display the items in that particular set. Note the "-00" after the name in the Entities list. This is 00 for most entity types (including Wells and Field), but when you have a file that includes completions or RFT data, the suffix identifies the sub-structure.

To remove entities from a set, simply highlight one or more names in the Entities list and then click on **Remove Items**. (Note: You cannot use this dialog to add entities to the list).

You can also rename a selection set. To do this, first type the new name in the text field, then press the Rename button above it.

To delete a selection set, first highlight the name and then click **Delete**.

5.3 USING SELECTION SETS

Now that you have a few sets defined and saved, what are you going to do with them?

The primary purpose of selection sets is to make selections! Use them to choose multiple items in a long list, particularly the one in the Filtering dialog. Close the Selection Set dialog to return control to the Filtering dialog and then choose the Sel Sets tab.

Make sure the Replace Selections option is selected. Then highlight each of your selection sets in turn and press **Apply**. You'll see how the items in the Selection List are highlighted accordingly. So while you used the list to create selection sets in the first place, you're now using the sets to select items in the list.

By now you may have also figured out that you can use selection sets to make *other* selection sets. For example, you could initialize the list using Replace Selections and SS001, and then change to Remove From Selections and choose the Low H2O set. You can also add two sets together using the Add to Selections option. The possibilities are endless.

When you get to the Grid plots, you'll see that selection sets can be used to control which wells are displayed in 2D and 3D.

In XY plots, they offer a quick way to filter the entities that appear. They also form the foundation for another powerful tool: **User Groups**.

N Elkevine	
V rittering	
Entity Type	Sorting
Wells 🔺	🔘 Ву Туре
Completions Field	By Entity Name
Groups/Areas	By Variable Value
Regions	
Gather Stations	Ascending
Quality/Target	O Descending
Aquifers	
Blocks	Variable TIME 🔹
segments ▼	Apply
Entity List	Name Values Sel Sets
GAS-05	SS001
OIL-02 OIL-01	L Names
OIL-03	Low H2O
OIL-04	
	Add to selections
	Remove from selections
	Replace selections
	Apply
	Make New SS Low H2O
Select All	Edit SS
	OK Help

5.4 SAVE CHANGES TO THE PROJECT FILE

Be sure to save changes to your Project File so you don't lose your selection sets!

CHAPTER 6: USER GROUPS

Simulator output often includes cumulative quantities for the entire field and one or more sub-groups of wells. These may be classified as separate entity types under the heading of groups, areas, or regions, depending on the simulator. Each set of cumulative values is saved as an individual entity and the data can be plotted just as individual wells are.

The User Group function lets you create your **own** new entities where the variable values are calculated from two or more wells. It allows you to choose which variables to include and whether to calculate them by summing or averaging the individual well values, or as ratios computed from the summed or averaged results. The new entities and variables are then added to the lists and they can be plotted using any of the XY plotting routines.

6.1 PREPARATION

In order to create user groups you must first define one or more selection sets. The wells to be combined are specified in the selection set. Only well entity types can be combined to create user groups – other types (field, RFT data, block data, etc.) will be ignored.

The selection set name will become the user group name, so you should name the selection set accordingly. Using the default selection set names is fine (i.e. SS001), but you may want to have something more descriptive.

The Selection Sets that were created in the previous exercise will work fine for this one.

6.2 CREATION

From the menu, select **Data** > **Groups/Patterns/Branches** to bring up this dialog.

The variables in the list are those associated with the current Well entity type. By default, all the identifiable production rate, injection rate, and cumulative values are placed in the "Variables to be summed" column, and all remaining values are in the "Unused variables" column.

This is provided as a starting point only. To change things, you simply highlight the variables that need to be moved, then use the [<] or [>] buttons to transfer them to a different list. For example, if you didn't want to include VPR and VPC values in your user group entities, highlight those names and press [>] to move them to the Unused variables column. In addition, you might also decide to average some of the pressure readings, so you could highlight BHP, WHP, and SWP in the middle column and then press [>] to move them to the "Variables to be averaged" column.

Croups/Patterns/B	Branches	—		
Solve <u>V</u> ariables to calculate				
User Groups WO GO	DR)R			
© Well Patterns	CT			
Branches	-1			
Variables to be U summed va	I <u>n</u> used ariables	Variables to be <u>a</u> veraged		
WPR OPR GPR VPR WPC OPC GPC VPC WIR OIR GIR VIR MIC	SOR WOR BHP WHP SWP SO1 SIR SLR STS WCT			
Selection Sets SS001 L Names L ow H2O	Use Select the wells ir pattern.	ion Sets to define 1 the group or		
	The set na the entity	me will become name.		
Create for: Active data set only				
OK Cancel Help				

Four items are included in the Calculate list. These values are calculated after all the others have been summed or averaged, and they depend on certain other values to be included in the calculations:

Meaning	Formula
Water / Oil Ratio	WPR / OPR
Gas / Oil Ratio	GPR / OPR
Water Cut	100 * WPR / (WPR + OPR)
Oil Cut	100 * OPR / (WPR + OPR)
	Meaning Water / Oil Ratio Gas / Oil Ratio Water Cut Oil Cut

By default, all four values are highlighted (meaning that they will be calculated), but you can change this as you wish.

Finally, the available selection sets are shown in the bottom-most list. Again, all of them are marked for inclusion by default, but you can change this and highlight only those you want to use to create new user groups.

To create the new user groups, make sure all your selections are as desired and click on **OK**. The dialog will close and a small progress dialog will be displayed so you can see how things are going. Once things are complete, the new user group entity names and variables will be added to the sidebars and you can immediately begin plotting the results.

IMPORTANT

When you create user groups, your selections *REPLACE* any existing user group entities. It isn't possible to add a single new user group to those created earlier. In general, most of the work to build user groups is in the creation of the selection sets, and the actual solution is done in a single operation.

6.3 SAVE THE PROJECT FILE CHANGES

If you save changes to your project file after creating user groups, they will be available the next time you load the project.

CHAPTER 7: XY EQUATIONS

In the preceding chapter on User Groups, you saw how new variables such as Oil Cut and Water Cut could be calculated from the other values that were recorded. Wouldn't it be nice to have this capability for other entity types?

You can! That's what XY Equations are all about. To access this function, use the menu to select **Data > XY Equations** and you'll see this dialog.

XY Equations	? 🗙
Equations - Double-click to change. Right click for options. Use [NEW] to create a new equation, or just start typing.	
[NEW]	Malle
	Completions
	Field
	Groups/Areas E
	Flow
	Gather Stations
	Quality/Target
	Aquifers
	Blocks 🖕
Enter Cancel	< <u> </u>
	All files
Variables - Double-click to insert into equation.	Active file only
BEG BAK <- != OR AND ROUND TRUNC DATE	Ignore /U errors
$\begin{bmatrix} \text{END} & \text{DEL} & - \end{pmatrix} = = \langle = \rangle = \begin{bmatrix} \text{SIN} & \text{COS} & \text{TAN} \\ APR \end{bmatrix}$	Apply
	Equation File
4 5 6 * < > ABS SIGN SQRT GIR	
1 2 3 - () LOG LOG10 EXP GOL	Load File
	Save File
	Save As
Close Help	Save AS

Data equations are used to compute new variables from existing XY values. You can create a single new variable or several. The new values will be included in the list of variables you can select for plotting. You can also use equations to modify existing variables.

7.1 WRITING EQUATIONS

Although equations can be much more complex than this, a basic equation might appear as:

... where *<operator>* includes (but is not limited to) standard operators such as +, -, /, and *. For example:

The new variable is named "GOR" and is defined as the ratio of gas production rate to the oil production rate. Both new and existing variable names are always surrounded by curly brackets { }.

You can also include constants and parentheses in your calculations, such as:

The capabilities of equations go far beyond these simple examples. A complete description of equations can be found in the appendix of the RS User's Manual. Although the instructions in the manual show the use of variable numbers to define equations (e.g., "V3" instead of "{WPR}"), we recommend always using explicit variable names. This will help avoid errors and will also make your equations generic so that they can be used with different projects.

The box at the top of dialog shows the equations already entered. The current equation is displayed in a line-edit control just beneath it, with the **[Enter]** and **[Cancel]** buttons to the right. To enter a new equation, you can simply begin typing in this field. You can also double-click the **[NEW]** line in the upper list box to automatically start a new equation.

You may simply use the keyboard to enter your equations, but the dialog offers many shortcuts to make your job easier. The variables that are found in your current data set are shown in a list box. Double-clicking on one of these will insert the variable name into the current equation at the cursor position, complete with surrounding curly brackets. As soon as you save an equation (using the **[Enter]** button) with a new variables, that name will also

be added to the list (even though you haven't solved it yet) so that it may be referenced in subsequent equations.

The most commonly used equation functions are also available on the dialog. Clicking on those will also insert them, along with parentheses with the cursor within, to facilitate the next entry.

7.2 SAVING AND LOADING EQUATIONS

Equations will be saved in your project file. However, it is also possible to save them to a separate file. This makes it easier to use them in multiple projects, without having to input them each time. The dialog contains buttons to Save As (where you can assign a new name to the file that will hold the equations), Save (to save changes to an existing file), and Load (so you can reload a previously saved file).

7.3 APPLYING EQUATIONS

Once you have your equations entered, you'll use the [Apply] button to solve the new variables. Before doing that there's a few things to consider.

If Tecplot RS detects that the variable used as the divisor has a range of values that include zero, it normally will not accept the equation because of the potential for divide by 0 errors. However, there is an option to "Ignore /0 errors". If this is checked, then any divide by 0 operation will be assigned a value of 999999.

Solving the water cut makes sense for well entities, but not for RFT records. For this reason, you also need to choose the entity types that will receive the new variables. This is done using the "Apply to" multi-select list.

Once the entity types have been chosen, click on the **Apply** button. Depending on the size of your current data set, the process can require anything from the blink of an eye to several minutes. Once complete, the new variables will appear in the selection list and can be immediately selected for plotting.



7.4 PROJECT FILE CHANGES

As usual, save changes to your project file. Although the XY equations themselves are saved in a project file, they are not automatically applied when it is loaded. You can, however, create a macro that includes the steps needed to apply the equations.

CHAPTER 8: CUSTOM PLOTS

You've seen how the primary filter limits both the entities and variables, and the secondary filter further limits the entity list. The XY Variables and XY Entities plot types give you the ability to quickly create plots using these filtered lists. You can even automatically create multiple pages of plots, scrolling through every entity or each variable.

Another level of control is achieved using the XY Custom plot type. With this option you can define exactly which variables are plotted for each entity *and in what order*.

You can choose any subset of values, effectively giving you a secondary filter for variables. You can even design an entire page where some frames display one variable and others may show multiple values. In addition, you can create different sets of these specifications, so that you could have a design for each entity type.

8.1 THE CUSTOM OPTIONS DIALOG

All these selections are made using the Custom Options dialog. This can be accessed from the menu bar under **Options > Custom Options.**

This dialog contains options similar to those in XY Variables. It includes controls for choosing the variables for each axis, including multiple Y axes and one or more variables on each.

Your custom plot definition will include the following:

- How many frames are shown for each entity. Each frame contains one plot. Note that this does not necessarily have to correspond to how many frames are shown on a single page. If you define 6 frames per entity, and set up your multi-plot options for 2 frames/page, the program will create 3 pages of plots per entity.
- For each frame, exactly which variables are shown and on which axes.

You start by defining the total number of frames. This is done in the small drop list labeled "Total". You may choose from 2 to 12 frames.

For each frame you must select the variable or variables you would like to display, and also which axis they should appear on. This operates identically to the selections made in XY Variables.

A list control is used to select which frames you are specifying:



For this exercise, you are going to do the following:

- Set a total of 6 frames.
- All frames will have Time on the X-Axis.
- Y-Axis variables will be as follows:
 - Frame 1: Gas Production Rate (GPR)
 - Frame 2: Water Production Rate (WPR)
 - Frame 3: Oil Production Rate (OPR)
 - Frame 4: Cumulative Gas Production (GPC)
 - Frame 5: Cumulative Oil Production (OPC)
 - Frame 6: Gas / Oil Ratio (GOR) on Y1 and Water/Oil Ratio (WOR) on Y2

If necessary, open the sample Chelan project file, then set up the Custom Plot options as described above. The illustration on the preceding page shows what the Custom Plot Options dialog should look like for frame 5.

8.2 CREATING XY CUSTOM PLOTS

Select **Plot Type > XY Custom**. The sidebar will show the available entities.

Access the Frames options and set things up for 4 multiframes in a 2x2 configuration.

🚺 Multi-Frame Options 🛛 🔀
Frame Mode:
Single Frame Multi Frame
Multi-Frames
Columns 2
Rows 2
☑ Link <u>G</u> rid View / Rotation
Link Inside Views / Blanking
✓ Link Layer Toggles
Link Well Toggle
Frame Spacing
2 % of Paper Size
0.25 Mi <u>n</u> imum (Inches)
Quick Plots
Location <u>A</u> rea (%)
Bottom of Page 30 ▼
Right Side of Page
Close Apply Help



For the FIELD entity, the first page of the display looks something like this:

Because your multi-frames options are set up for 2 x 2 frames, only the first four of the six frames you specified are shown.



Pressing the Next button [>] brings up the remaining frames:

You might prefer to set up your multi-frames options to a 3 x 2 frame layout, so that all frames for the selected entity are displayed on a single page:



By combining the options in Filters, Multi-Frames, and Custom Plots, you can create plots that display only the variables you want, choose the order they appear, and limit which entities are output.

The Play Button

To quickly view all the pages, highlight the first entity in the list and then press the Play

button. The program will automatically scroll through each page.

If the animation is a bit too fast, you can slow things down. Access Plot Options and choose the first tab (Load / Save). The animation speed is controlled by a slider:

Load / Save Variables XY Lines XY Axes Grids Grid Legend Grid Axes Cell Labels Wells Current Style: From project file	Plot Options								×
Current Style: From project file Load at startup Load Misc Settings Default time variable Time Date format 2000.50 Time format 40.75 Anjimation step delay Short Long	Load / Save	Variables	XY Lines	XY Axes	Grids	Grid Legend	Grid Axes	Cell Labels	Wells
Animation step delay Short Long	Current Style: Load at startu Load Save Save Reset Defaults	From project P Misc S Defau Date Time 1	ct file Settings ult time variabl <u>fo</u> rmat 2000 format 40.7	e ○ <u>T</u> ime					
	Арріу	A <u>n</u> ima	tion step dela	Short					Long

Want to print your plots or record to a file them for display outside of Tecplot RS? See Appendix C of the RS User's Manual for a discussion of output options.

8.3 SAVE PROJECT FILE CHANGES

When you update your project file with the recent changes, the settings for custom plots will be saved.

CHAPTER 9: COMPARING XY DATA SETS

It is often useful to be able to compare data from two or more files. The separate data sets may be simulator output versus observed values, or perhaps multiple simulator runs. Tecplot RS contains tools to allow you to display comparison data in several different ways.

9.1 LOADING MULTIPLE DATA FILES

Since the data sets to be compared are stored in different files, you must start by loading at least two. You can load hundreds of XY files at once if needed, and you can choose files from among all those loaded for display and/or comparison.

Start with the Chelan project file that you have been using for the preceding exercises. If multiple frames are being displayed, use the Multi Frame Options dialog to switch back to a single frame.

Click on **Project > Load XY Data** or use the button on the toolbar, and then use the **Add...** button to bring up a file browser.

The first file you loaded was a Unified Summary file from the Eclipse simulator. This time, you're going to choose a History file, which contains the actual recorded output. This will allow you to compare recorded and simulated data.
Using the drop-down on the browser dialog, change the filter to "Eclipse(SLB)/Chears files". If needed, browse to the Examples folder which will be in under the folder where Tecplot RS was installed. Then select chelan.hist and open the file.



The Active Data Set

When you load multiple files, you must designate the **active** data set. Only one data set may be designated as active. The active data set is the one that will be displayed by default in all plots. When comparing data sets, the active set will be the one the others are compared *to*, and the active data set will determine which entities and variables appear in the selection lists.

Chapter 9	9	Comparing	Data	Sets
-----------	---	-----------	------	------

Since you now have two data sets loaded, the Manage Data dialog will pop up:

🚺 м	anage D	ata				×
Curre	ent Proje	ct File:				
C:/Pi	rogram Fi	iles/Tecplot/TecRS	20xx Rx/ch	elan.rsprj		
XY	Grid	I Templates	Macros	Unload		_
Ac	tive Data	a Set:				
F. Vi S /e	ILE NAME IELDS : 1 /ELLS : 5 TATE FILE examples,	E : chelan.unsmry I E : C:/Program Fil /chelan.rsxsx	es/Tecplot/Te	ecRS 20xx Rx		
Dis Av	splay As vailable X1	chelan.unsmry Y Data <u>S</u> ets:			Update	
	:helan.u :helan.h	nsmry C:\Prog ist C:\Program	ram Files\To Files\Tecplo	ecplot\TecR ot\TecRS 20;	S 20xx Rx∖ex xx Rx\examp	a bli
					•	
			C	OK	Help	

This dialog is used to designate the active data set, which is the one highlighted in the list at the bottom of the dialog. You can also see basic information about the highlighted file in the upper portion of the dialog.

By default, your original data file (chelan.unsmry) file will remain active, and you'll want to leave it that way for this exercise.

9.2 COMPARING DATA SETS WITHIN A FRAME

The first approach for comparing data sets is to plot them in a single frame, usually using a different line style for each. This can be done using the XY Variables, XY Entities, RFT, or XY Custom plot options. All those sidebars contain these controls:

Data Set		
Compare	Delta	Options

For this exercise, we'll use XY Variables. Change to this plot type if needed. Select the OIL-01 entity and WPR for the variable on the Y1 axis.

Now turn on the Compare toggle. Your plot is immediately updated to show both the active and comparison data sets:

💟 Tecplot RS		
Project <u>E</u> dit <u>V</u> iew P <u>l</u> ot Type <u>T</u> emplates <u>y</u>	<u>G</u> allery <u>D</u> ata <u>O</u> ption:	s <u>I</u> nsert <u>P</u> lot F <u>r</u> ame <u>A</u> nalyze <u>M</u> acro <u>H</u> elp
🗋 📲 🐺 🖼 🕼 💭 🔍 🭕	🗣 🗳 🌽 🖣	🕌 🗩 💽 🍾 Ab 🚣 🏭 🖻 🕼 🎬 🏭 🔨 🏥 🐘 🔠 Jar Joy 🕉
XY Variables 🗗 🗙		
☑ Lines Filter		WPR
Symbols Reload		
Entities		M/DR chalso upon ty
011-01		WPR-chelan.hist
OIL-03		
OIL-04	30	
FIELD	-	t
	25	
	20	
Properties		4t
V. DATE	e 15	
	8 13	
Y1: Y2-5: 2 🔻	ļļģ	
VIR A TIME A	10 -	
VPC DATE	l at l	
WCT APR	5	
WHP BHP	3	
WIR GIR		
WOR E GLR	05 02/40	100 44/42/4072 05/06/4070 40/06/4004 04/40/4000
WPC GOI	03/23/19	Date 04/10/19/0
		Date
Data Set		
Compare Delta Options	chelan.unsmry	26 Jun 2018
VV Vsvisblar		
Click to Select, Drag to Select Group		

A different line style is used for each data set, making it possible to see which is which.

Altering Styles for Comparison Data Sets

In Chapter 2 you got a brief introduction to Plot Options, where you were able to change the line thickness and symbols for plotted lines. Now you'll see how to use Plot Options to help differentiate the lines for each comparison data set. On your plot, double-click on the blue line representing WPR for the active data set. This should bring up the Plot Options dialog as shown here:

💟 Plot Options							×
Load / Save Variables X	Y Lines	XY Axes	Grids	Grid Legend	Grid Axes	Cell Labels	Wells
Style set: Active	•	✓ Lines					
<u>V</u> ariable:	÷	Color	Defau	lt		•	
SWP	*	<u>P</u> attern	Defau	lt		•	
VIC		Le <u>n</u> gth	1%			•	
VIR VPC		Thickness	0.40				
VPR		Symbols					
WHP		Color	Match	Line		•	✓ <u>Fill</u>
WIC WIR		Shape	Defau	lt		•	
WOR	Ξ	Spacing	D = 4	%		•	
WPR		Size	1.00				
	*						
						Multi-Edit S	tyles
						lose	Help

Note that the Style Set option list is set to "Active". The settings you see are used when plotting WPR for the active data set.

To see the settings used for the comparison data set, use that drop list to select "Comp 1". Alternatively, double click on the orange line on your plot. The settings should now appear as:

Plot Options							×
Load / Save Variables	XY Lines	XY Axes	Grids	Grid Legend	Grid Axes	Cell Labels	Wells
Style set: Comp 1	•	✓ Lines					
<u>V</u> ariable:	+	<u>C</u> olor	Oran	ge		•	
SWP		<u>P</u> attern	Short	t Dash		•	
VIC		Le <u>n</u> gth	1%			•	
VIR		<u>T</u> hickness	0.40				
VPR		 S <u>v</u> mbo	s				
WHP		Colo <u>r</u>	Matd	h Line		•	✓ <u>F</u> ill
WIC WIR		S <u>h</u> ape	Defa	ult		•	
WOR	=	Spacing	D = 4	1%		•	
WPR	_	Size	1.00				
	*						
						Multi-Edit S	Styles
L						Close	Help

Two things are different from the styles for the Active data set: The line color is Orange, and the line pattern is Short Dash.

You may prefer different settings, such as maintaining the line color and changing only the symbols. There are many options that will help differentiate comparison data sets, such as:

- Make the line thicker on the active data set and thinner on the comparison set.
- Turn symbol fill on for the active set and off for Comp 1.
- Show only symbols on Comp 1 (turn off the Show toggle for lines), and show only lines on Active (turn off the Show toggle for symbols).
- Make your symbols square for one set and diamonds for the other.

These are just a few of the many ways you can have Tecplot RS vary the styles between the active and comparison data sets.

Note that there are also multiple Comp # options, allowing you to do comparisons of additional datasets with styles changing for each.

The Delta Option

When comparing data sets in XY Variables or XY Custom, you may also turn on the Delta toggle. This changes your plot so that the values represent the difference between the active and the comparison data sets. The line for the active data set is unchanged and may be plotted for reference, but the lines for the comparison data sets are computed as the difference between the comparison data set and the active. NOTE: The Delta toggle is not offered for comparisons in the XY Entities and RFT plot types.

YOU SHOULD KNOW When doing comparisons it is generally best to use DATE (rather than TIME) as the X-Axis variable. This is because the TIME values often start at 0 but are measured from different references, so that identical time values may actually not be measured at the same physical time. Dates do not have this problem.

If you want to use TIME, then simply ensure that both files reference the same starting point.

9.3 WHAT CAN BE COMPARED ?

Remember that the list of entities and variables in the dialog come from the active data set, and these may be reduced using the selections from the Filter dialog.

When you select an entity name from the sidebar, that entity is guaranteed to exist in the active data set since this is where the list comes from. The program then looks for an entity of the same name in the comparison data set(s). When using this comparison option, entity names MUST match exactly, otherwise no comparison line is drawn.

There is some flexibility with matching variable names, however. It is not unusual that files from different sources would use different names for the same quantity. For this reason, Tecplot RS allows **variable aliases**. The rsvariables (simulator option) file defines a starting set of variable names and aliases, but you can alter or expand these for each project.

To see the aliases along with other settings that originated from rsvariables, use the Variables tab on the Plot Options dialog.

Load / Save Variables	XY Lines	XY Axes	Grids	Grid Legend	Grid Axes	Cell Labels	Wells
Master variable list	Aliases						
✓ Sort ✓ Active	Long name	Wate	r Prod Rate				
ST9 STS	Alias <u>1</u> Q	WP	Alias 2		Alias <u>3</u>		
SWP	Default Sty	/les					
VIC	Line <u>c</u> olor	Blue		 Symbol color 	Blue	•	
VPC	Line patter	n Solid		 Symbol shap 	e Circle	•	
VPR							
WCT WHP WIC	RSVariable	s					
WIR WOR	Eclipse/SLE	3				Change	
WPC WPR	C:\Program	n Files\Tecplo	t\TecRS Be	ta \rsvariables_ecl	ipse.txt		

When searching the comparison data set for the variable to be plotted, the program first looks for the one that matches the name used in the active data set. If a match is not found, it checks to see if any aliases have been defined for that variable, and searches the comparison data set for a match with those. In the dialog shown above, if we selected "WPR" (the standard mnemonic for Eclipse simulators) as the variable to plot, and this was not found in the comparison data set, the program would also look for "QWP" (the standard mnemonic used by VIP).

You can designate a total of three variable aliases. This won't be required for this exercise, since the provided file does not require them, but you now know where to go when you need to set up variable aliases.

9.4 COMPARING DATA SETS IN XY FREESTYLE

The methods described above create lines for two or more data sets in a single frame. This approach is very automated, but it has some limitations in that entity names and variable names must match.

The **XY Freestyle** plot type offers another way to do comparisons. It's not quite as automated as the Compare toggle. In freestyle mode, each line plotted must be individually selected. However, it is completely flexible, allowing you to do such things as place comparisons in side-by-side frames, compare entities with different names, define unique styles for each line, etc.

Start by using the Multi Frame option to set up 4 frames in a 2x2 arrangement. Then select the XY Freestyle plot type. Initially, your plot will display an error message in all frames. This is OK and is because you haven't specified the variables for the plot.

Tecplot RS		
Project <u>E</u> dit <u>V</u> iew P <u>l</u> ot Type <u>T</u> emplates	<u>G</u> allery <u>D</u> ata <u>O</u> ptions Insert <u>P</u> lot F <u>r</u> ame <u>A</u> nalyze <u>M</u> acr	o <u>H</u> elp
- 📄 🔡 📅 📅 🎧 🔚 🔍 🗸	🗘 🗳 🦾 🕵 ᡗ 🕥 🕟 🦘 🗛 📲 🖻	🕋 🏭 🖓 🗥 🎬 🐘 🔢 Set f(x) 🕉
XY Custom Freestyle 🗗 🗙		
Symbols		
Page 1 🜩 + - C		
Frame 3 🜩 + - C		
Line 1 🜩 🕂 - 🗾		
Layout	Variables and/or entities have not vet been selected	Variables and/or entities have not yet been selected
File chelan.unsmry	OR selected variables do not exist for the chosen entity.	OR selected variables do not exist for the chosen entity.
Entities 🕂	HINT: Use Filter to limit variables to certain types.	HINT: Use Filter to limit variables to certain types.
OIL-01		
OIL-02 OIL-03		
OIL-04		
GAS-05		
FIELD		
Properties		
X-Axis:		
M-Avie:		
1-74.03.	Variables and/or entities have not vet been selected	Variables and/or entities have not yet been selected
	OR selected variables do not exist for the chosen entity.	OR selected variables do not exist for the chosen entity.
	HINT: Use Filter to limit variables to certain types.	HINT: Use Filter to limit variables to certain types.
Line Stule		
Type: Apply to:		
Variable 👻 New Lines 👻		
Apply	chelan.unsmry	26 Jun 2018
XY Freestyle		
Click to select, Drag to select broup		h.

In **XY Freestyle**, you can create multiple pages, with multiple frames on each page, and any combination of plots within each frame. For this exercise, you're going to do side-by-side comparisons of two variables (OPR and WPR) on the FIELD entity from the two files that are currently loaded (the history and simulated data).

To do this, follow these steps:

- 1. Set options for all plots:
 - a. Page = 1
 - b. Line = 1
 - c. Entity = FIELD
 - d. X-Axis = DATE
- 2. For Frame 1, choose:
 - a. File = chelan.unsmry
 - b. Y-Axis = OPR
- 3. Change to Frame 2 and choose:
 - a. File = chelan.unsmry
 - b. Y-Axis = WPR
- 4. Change to Frame 3 and choose:
 - a. File = chelan.hist
 - b. Y-Axis = OPR
- 5. Change to Fame 4 and choose:
 - a. File = chelan.hist
 - b. Y-Axis = WPR

Hint: When changing to a different frame, you can enter the desired frame number directly into the Frame field, use the small up/down buttons next to the field to advance to the next frame, or simply click inside the desired frame in the plot.



Your plot should look something like this:

Feel free to experiment with adding more maps, frames, and pages. You can also doubleclick on the lines to change styles.

CHAPTER 10: RFT PLOTS

RFT data are basically the same as the observed data that come from the Eclipse.unsmry or similar files. The primary difference is that with RFT data the independent variable is depth instead of time. While RFT data can be plotted using any of the three basic XY plotting functions (XY Variables, XY Entities, and XY Custom), Tecplot RS includes a specialized module for RFT data that simplifies some of the selections.

10.1 LOADING RFT DATA

Since they are stored in separate files, RFT data must be loaded separately. Start by bringing up the XY file loading dialog, then click on the ADD button to bring up the browser. From the list of file types, select "VIP files." You may then load the chelan.frft file that was included with the sample files installed on your system.

When you click OK in the Load XY Data dialog, Tecplot RS will ask if you want to append the RFT data to the current data set. Click **Yes**.

Next, the Manage Data dialog will be displayed. You may notice that the RFT file you just loaded does NOT appear in the list of available data sets. However, if you look at the top of the dialog, you'll see that the active data set (chelan.unsmry) now indicates that the RFT data have been *appended*.

Tecplot RS groups the RFT data into its own entity *type*, just as wells, regions, quality data, etc. are types. The Filter options also include the RFT type.

By appending RFT data to the current data set, you make it easier to access and switch between plot types. Hit the Save button to update your Project File so that the RFT data will be loaded the next time you use the project.

🚺 Man	age Data	3			
Curren	t Project I	File:			
<none< td=""><th>></th><th></th><td></td><td></td><td></td></none<>	>				
XY	Grid	Templates	Macros	Unload	
Activ	e Data Se	et:			
RFT FIEI WEI RFT STA	FILE : d .DS : 1 .LS : 5 DATA : 7 TE FILE : amples/ch	helan.frft '1 C:/Program File elan.rsxsx	s/Tecplot/Te	cRS 20xx Rx	
<u>D</u> ispl Avail	ay As d	nelan.unsmry ata <u>S</u> ets:			Update
ch	elan.unsi	mry C:\Progr	am Files\Te	cplot\TecR	S 20xx Rx∖exa
ch	elan.hist	C:\Program	Files\Tecplo	ot\TecRS 20>	∝ Rx\exampli
			~		
				OK	Help

10.2 RFT PLOTS

Choose Plot Type > RFT to switch to the RFT sidebar.

As with other plot types, you can plot a single line or several. For RFT plots, the multiple lines show data at various dates. Remember that time/date are NOT the independent variable in this data type – DEPTH is. So each time is shown on a separate plot line.

By default, RS selects DEPTH (the independent variable) for the Y-Axis, and PRESSURE (the first dependent variable) for the X-Axis.

Your job is to select well OIL-01 for the entity to plot, and to choose one or more dates for which a plot is desired. For this exercise we'll use years 1972 – 1974.





Note that the Y axis is inverted so that values increase downward, a more natural way to visualize depth.

Save Gallery Plot #3

It's time to save another gallery plot. Use **Gallery > Save** and name this one **RFT Pressure**. Then save your project file by clicking on the save icon or selecting **Project > Save** from the menu. In Chapter 12 you'll make use of your saved plots.

10.3 COMPARING RFT PLOTS

You may compare RFT data from two or more files. Chapter 9 describes the basic operation for comparison plots.

When searching for a match between the active data set and the comparison data set(s), the program must look at both the well name and time/date identifier. The well names must match exactly, but it would be unreasonable to expect that dates or times would be identical. For this reason, when searching the comparison data set for a match, the program will find the time *closest to* the one selected for the active data set. The time will be reflected in the legend so that you can see which measurements are being used.

In general, it is better to set your time units to Date, as this removes the ambiguity caused with time (days) values.

The delta option is disabled when comparing RFT data.

CHAPTER 11: COMPLETION PROFILES

As with RFT data, completion data may be plotted using any of the standard XY plotting functions. However, Tecplot RS provides a different view and a simplified interface for completion data, designed to compare results from each completion in a single well.

The data files you have been working with thus far do not contain completion data, so we'll need to load another data set. Use the XY File loader to load the completions.unsmry file. This will be in a sub-folder names "Completions" under the Examples directory where you found the Chelan data.

After loading the new data set, the Manage Data dialog will be displayed. You will need to make the new data set active by highlighting it. You'll also see in the information area that this data set contains 29 completion entities.

Manage Data
Current Project File:
C:/Program Files/Tecplot/TecRS 20xx Rx/chelan.rsprj
XY Grid Templates Macros Unload
Active Data Set:
Pile NAME : Completions.unsmry COMPLETIONS : 29 FIELDS : 1 WELLS : 12 Display As completions.unsmry Update
Available XY Data <u>S</u> ets: chelan.unsmry C:\Program Files\Tecplot\TecRS 20xx Rx\examples\chelan.unsmry
chelan.hist C:\Program Files\Tecplot\TecRS 20xx Rx\examples\chelan.hist
completions.unsmry_Cttprogram Filest lecplot tecks 20xx kxtexamplestCompletionstcompletions.unsmry
۲
OK Help

After dismissing the Manage Data dialog, select **Plot Type > Completion Profiles** to bring up this sidebar:

The list of wells is automatically limited to those containing completion data. These appear in the first list box. The number in parenthesis indicates the number of completions in each well.

The available times are shown in the center list box. Each plot will reflect values at a selected time. The display of days versus date is determined by a setting in Plot Options on the first tab.

The variable to be plotted is selected at the bottom of the sidebar.

To start, make the selections as shown here.

Completion Profiles				Ð	x
📝 Lines					
V Symbols					
Wells				- 4	Þ
AMZ101 (2)					
AMZ102 (4)					1
AMZ103 (3)				=	
AMZ104 (2) AMZ105 (2)					
AMZ105 (2)					1
AMZ107 (3)					
AMZ108 (2)				-	
4					
Times					
24 Jan 1990					
24 Feb 1990					
27 Mar 1990 26 Apr 1990					
27 May 1990					
26 Jun 1990				-	1
27 Jul 1990					
27 Aug 1990				-	·
4					
Properties					-
X1:		X2-3:	2	•	•
IWIR		BHP			
IWOR		GOR		=	
NDC		GPR			
PRC		IGIR			
SG	Ξ	IGOR			
SO		INDC			
SW	Ŧ	IOIR		-	
Show Percent					
Label: None 🔻	•				
Completion Profiles			-	0	
	_				

The resulting plot will look like this.



The bars give you a clear picture of how each completion is contributing to the total well production.

This plot shows only Oil Production Rate, but you can select up to three different variables for display. It is generally best to show each variable on a different axis, especially if their units and/or ranges vary significantly. This works just like it did in the XY Variables exercise.

In the second list box containing the variable names, choose WPR. Then change the dropdown menu that is labeled "X2-3" to select axis 3 and select GPR.

Now your plot should look like this:



Save Gallery Plot #4

Once again save a gallery plot, and name this one **Completion Rates**. Again, be sure to save your project file.

CHAPTER 12: PLOT GALLERY

In previous chapters you've been directed to use the **Gallery > Save** function to save several plots. It's now time to see what this can do for you.

If needed, load the Chelan project file that was saved in the preceding chapters. Then **Select Gallery > Manage** from the menu. This should bring up this dialog:



Here you see the four saved gallery plots. Plots are grouped by plot type, which helps when managing large numbers of plots. The groups can be individually expanded and collapsed using the controls next to the group name.

If your dialog does not include all these plots, it is probably because you failed to save the project file. Gallery plots are saved only when the project is saved.

To display a plot, you can either highlight it and click Display, or simply double-click on the name. You should do this now for each of the saved plots. Note that when you display a plot, not only will you see the same image as when it was saved, but the sidebar will also update to reflect the plot type and all the selections made. That's because gallery plots are not simply an image, but record the "state" of the program. This means you can use gallery plots to get back to where you were when the plot was created, and perhaps continue work or use them as a starting point for creating new plots.

The Plot Gallery manager dialog also includes buttons that will allow you to export, print, or delete the highlighted plot, plus a Save button that is identical to using the Save option from the menu. The dialog is 'modeless', meaning that it can remain open while you do other work (although you'll probably want to move it off to the side).

The ten most recently used gallery plots are also displayed under the Gallery pull-down menu, and you can display them by clicking on the name there.

Gallery Plots save every selection needed to reproduce the state of RS when you saved them, with one exception. Selections made in the Plot Options dialog are saved only once as part of the project file. In other words, Plot Options are a 'global' setting for the project, and any changes made there will be reflected in ALL gallery plots that are part of that project.

2D and 3D grid plots can also be saved in the gallery, so as you move into those exercises, be sure to save some plots and experiment more with the gallery.

CHAPTER 13: FLOW TABLES

The Flow Tables function requires that you be familiar with CHEARS flow table (.flot) files.

Flow table plots display the information in one or more *.flot files. Flow tables contain an N-dimensional array of bottom hole pressure (BHP) values plotted for N-independent variables. BHP is shown on the Y-axis of the plot. Flow tables also include a dependent variable which Tecplot RS places on the X-axis. (Dependent variable applies to the flow table, not to the Tecplot RS plot.) Flow tables are plotted by creating XY-slices from a combination of independent variable settings.

13.1 LOADING FLOW TABLE DATA

Flow table data are very different from the data sets used in the other XY plotting options. Because of their uniqueness, they are not loaded from the standard File Loading dialog but are instead accessed through the Flow Table sidebar (select **Plot Type > Flow Tables**):

Pressing the **Load...** button will bring up the standard file selection dialog that will allow you to choose the .flot file to be loaded. Chelan.flot is included in the example files installed with Tecplot RS, and you can load it now.

You may load more than one flow table file at a time. If you do so, you may find it helpful to turn on the Show Source File toggle. This will show the file name along with the flow table number.

Once loaded, flow tables can be removed using the Unload button.

Lines Symbols Flow Table CNo flow tables loaded> Load Unload Show Source Mult: Not Available Not Available Not Available Unitie Not Available Unitie Uni	8
Symbols Flow Table No flow tables loaded> Load Unload Show Source Multi: Single: Not Available Not Available Not Available	
Flow Table No flow tables loaded> Load Unload Show Source Multi: Single: Not Available Not Available	
<no flow="" loaded="" tables=""> Load Unload Show Source Multi: Single: Not Available Not Available Not Available</no>	
Load Unload Show Source Multi: Single: Not Available Not Available	
Multi: Single: Not Available Not Available Not Available	
Not Available Not Available	
vel ivoe:	
real type:	
Dep. Variable:	
Flow Tables	

13.2 THE FLOW TABLES SELECTIONS

not controlo	₽×
☑ Lines	
Symbols	
Flow Table	
1037	
Load Unl	oad
Show Source	
Multi:	Single:
WHP 🔻	WCT -
300.	.00
500.	25
	.2.
700.	.50
700.	.50 .75 .99
Well Type:	.50 .75 .99
Well Type: Producer Den Variable:	.50 .75 .99
Vol. Well Type: Producer Dep. Variable: LIQ	.50 .75 .99
V00. Well Type: Producer Dep. Variable: LIQ	.50 .75 .99

Once data are loaded the sidebar will show the available variables and options.

The Well Type (injector or producer) and dependent variable are determined by the data file. They are displayed on the sidebar for reference.

Flow Table Number

You must select one flow table number to view from the Flow Table Number list box. Changing the flow table number may cause the options in the remaining list boxes and option menus to change, since each table may have different dimensions.

Multi

When a variable is selected in the Multi drop-list, the list beneath shows all the associated independent values of the selected variable. From this list you may select one or more data values. Each will be shown on the plot using a different line color.

Single

There may be one or more variables listed in the drop-list under the Single heading. As you choose each one, the list box beneath will display the independent values for that variable. You should choose one value for each of the single variables. These selections will determine the data to be plotted. Your choices will also be reflected in the plot title:



CHAPTER 14: SETTING AXIS RANGES AND SCALES

14.1 FRAME RANGE

In preparation for the next exercise in this section, please be sure the chelan.unsmry file is loaded and is the active data set. Set up the multi-frame options to display a total of 4 frames in a 2 x 2 arrangement.

Select the XY Variables plot type and choose OIL-01 as the first entity and GPR (Gas Production Rate) as the Y-axis variable.

Look at the ranges shown on each of the 4 frames and note that the upper limit varies in each (anywhere from 800 to 5000). The ranges selected for each frame are, by default, chosen to 'fit' the data being displayed.



Now double click on the Y-axis title - the text that says "Gas Prod Rate (MSCF/DAY)". This should launch the Plot Options dialog with the XY Axes tab selected and GPR highlighted in the Variable list:

This page of the Plot Options dialog allows you to control the axis styles and limits for XY plots. The settings are unique to each variable, so that you can tailor the options accordingly.

For our default plot, the selected Range option is "Frame", meaning that the axis range will be determined by the

.oad / Save Variables XY Lir	nes)	T AXES Grids	Grid Legend	Grid Axes	Cell Labels	Wells
<u>/</u> ariable:	+	Axis Scale				
GLR		<u>R</u> ange	Frame	•	Scale 1	•
GLRH		Min	0			
GMR						
GMT		Ma <u>x</u>	1000		Unit override	
G01		Interval	0			
GOR			_			
GORI		Minor markers	1			
GP		Avis Style				
GPC		Axis Style				
GPGR		Axis <u>c</u> olor	Match Line 🔻	Label color	Match Line	•
GPI		Major markers	Solid Lines 🔻	Font	Helvetica Bold	-
GPR				-		
GPRA	-	Minor markers	Ticks Only 🔻	Size	2.00	%
Long names						
Apply						
Apply						

data shown in each individual frame. This is fine for getting the greatest amount of detail, but not terribly useful for comparing multiple entities in side-by-side frames.

14.2 DATA RANGE

For this exercise, change the Range option to "Data". This option tells Tecplot RS to set the axis range to fit the minimum and maximum for *all* entities *of a single type*. This works within entity types so that the FIELD range (generally the sum of all wells) doesn't skew the ranges for individual wells.

You'll need to click on the **Apply** button in order to see your changes. When you do, your plot should look something like this:



Now all four frames have a range from 0 to 5000, making it easier to see the values of each well relative to the others.

14.3 MANUAL RANGE

The third option in the Range pull-down menu is "Manual". When you select this, three text boxes labeled Min, Max, and Interval will be activated. We'll use these to input our own range, overriding the calculated values.

Enter 0 (zero) as the Min value and 10000 in the Max box. In the Interval box, enter a value of 500. Then click on **Apply** to see this plot:



The lines appear flattened because we've scaled to a much larger range. The axis labeling interval is also much tighter, showing major grid lines every 500 feet. NOTE: Leaving the interval at 0 (zero) would have instructed RS to compute a 'nice' interval. When specifying an interval other than 0, Tecplot RS will give you exactly what you request.

14.4 AXIS SCALES

Another option on the XY Axes tab of the Plot Options dialog is to define a scale factor to be applied to the plot axes. By default, this is set to 1 meaning that no change is made. You can use scale factors to shorten the axis labels (e.g. to show values in thousands of barrels instead of barrels). They can also be used to convert the plot to different units of measure, such as English to metric.

For example, our GPR values are expressed in MSCF (thousands of cubic feet). We can change this to cubic meters by specifying a factor of 0.03531467 (there are 35.31467 cubic feet in 1 cubic meter, and then we divide by 1000).

Axis Scale			
Range	Data 🔹	Scale	Enter 🔹
Min	0.000	📃 Log	0.03531467
Max	10000.000	🔽 Unit (override
Interval	500	m3	
Minor Markers	1		

For this exercise, first set the Range option back to Data. Change the Scale option to "Enter", and the enter the value 0.03531467 in the text box beneath the scale options.

We'll also want to reflect the new units in the axis label. To do this, check the "Unit override" toggle and then enter "m3" in the text box that appears.

Finally, click on **Apply** to see the results.



14.5 LOG SCALES

The final option available for scaling the grid axes is a logarithmic scale. For this exercise first choose OPC (Cumulative Oil Production) from the variables list in the sidebar in order to display this on your plot, and then double-click on the axis label to highlight OPC in the Plot Options dialog.

Toggle on the "Log" option (leave the scale value at 1), and then press **Apply**. Your first frame should look like this:



As you can see, there are many things you can do to customize the appearance of your plots.

14.6 SAVING PLOT STYLES IN A NAMED FILE

There are many customization settings in the Plot Options dialog, and setting things up exactly as you want may take some time. If you click on the Save button, all the settings you made in this section will be saved to your current Project File and will be used the next time you open that project.

Many Plot Options settings are not limited to a specific project, though. In particular, line styles and paper layout templates (covered in Chapter 2 of this guide) are often company-wide standards. You don't want to have to repeat your changes every time you start a new project.

Happily, you don't have to. All your Plot Options settings can be saved in a named file and used as a default starting point whenever you create a new project.

To do this, bring up the Plot Options dialog and choose the Load/Save tab.

Click on **Save As...** and enter a name and location for a file that will hold the style settings. Once this is saved, check the "Load at startup" toggle. This will instruct RS to use these styles any time you start a new project.

💟 Plot Options								×
Load / Save	Variables	XY Lines	XY Axes	Grids	Grid Legend	Grid Axes	Cell Labels	Wells
Current Style: Load at sta Load Save Save As Reset Default	Factory def rtup Misc S Defau S S Time 1 Anima	aults iettings Ilt time variabl <u>f</u> ormat 2000 format 40.71 ation step dela	le () <u>T</u> ime <u>0</u> <u>D</u> ate .50 5 					
			Short					Long
Арріу]							
							lose	Help

You can also use this feature to share Plot Options styles between projects. The **Load...** button will open project files as well as files saved from the Plot Options dialog.

CHAPTER 15: LOADING GRID DATA

Tecplot RS has many sophisticated functions for plotting both 2D and 3D representations of a reservoir model. Your first step will be to load a file containing the data you wish to plot.

If you did the XY examples in the first part of this tutorial and have an existing Chelan project file, make sure it is open. This will allow you to add the new grid data to the existing XY data.

15.1 LOAD GRID DIALOG



To load most grid data, you can use either **Project > Load Grid Data** or the toolbar button. This will bring up a browser that is used to choose the appropriate file.



For data in the NEXUS VDB format, instead of a file name you'll be selecting a case folder directly under the .vdb folder. Use the separate button or menu option for VDB data. This will bring up a folder browser.

Grid File Types

RS supports a variety of data formats for grid data. At the time of this writing, these include:

- Eclipse/SLB (also includes CHEARS)
- CMG (available on Windows platforms only).
- Sensor Map
- UTCHEM
- VIP Map files (older NEXUS format)
- VDB folders (newer NEXUS format)

New loaders are added regularly – check with your Tecplot representative for an up-to-date list.

When the file browser is launched the filter will include options for each type. The sample data files included in your Tecplot RS installation are Eclipse/SLB format, so choose that if needed. Then choose the chelan.grid file from the examples folder.

💟 Open File					×
○○	Program Files	xx Rx 🕨 examples 🕨 👻	Search	examples	٩
Organize 🔻 🛛	New folder			= •	0
⊳ 🜟 Favorites	Name	Date modified	Туре	Size	
	퉬 comparisons	7/11/2016 1:13 PM	File folder		
Distribution in the second	Completions	7/11/2016 1:13 PM	File folder		
	🎉 streamlines	7/11/2016 1:13 PM	File folder		
🛛 🖳 Computer	chelan.grid	7/8/2016 1:03 AM	GRID File	507 KB	
	📄 quinaultIgr.grid 场	7/8/2016 1:03 AM	GRID File	151 KB	
🖻 🗣 Network	📄 radial.grid	7/8/2016 1:03 AM	GRID File	1,055 KB	
	File <u>n</u> ame: chelan.grid		✓ Eclipse(S	LB) Grid (*.*gr*)	•

After you open the file, you'll see this dialog:

:/Program	Files/Tecplot/TecRS 20xx Rx/examples/chelan.grid
Make <u>a</u> ctive	
Files Opti	ons
<u>I</u> nit file	C:/Program Files/Tecplot/TecRS 20xx Rx/examples/chelan.init
<u>R</u> estart file	C:/Program Files/Tecplot/TecRS 20xx Rx/examples/chelan.unrst
<u>X</u> Y file	C:/Program Files/Tecplot/TecRS 20xx Rx/examples/chelan.unsmry
<u>D</u> isplay name	chelan
<u>S</u> treamlines	
Sur <u>v</u> ey wells	

The Eclipse data are actually found in three or more files. These include:

- .grid Grid file, containing the grid geometry.
- .egrid Alternative format for the grid geometry
- .init Init file, containing static properties such as porosity or permeability.
- .unrst Unified restart file, containing time-dependent values such as pressure and oil saturation.
- .Xnnnn Individual restart files, which contain each time step in a separate file.

You normally need to browse to only the grid file name. The program will automatically find the additional files as long as the root names match that of the grid file. You'll see that the init and unrst files were found and filled in for you.
You may also notice that the unsmry file containing the XY data was also found. When loading grid data, you have the option of loading a single XY file along with it. You can clear this field if you don't want the XY data loaded, or use the [...] button to browse to a different file. Don't worry if the XY data for this file are already loaded; Tecplot RS will detect this and won't load it a second time.

The options shown on the Files tab of this dialog are specific to loading Eclipse grids. Had you chosen files from a different simulator type the options would be a bit different. See the User's Manual for a description of each type.

There is a separate Options tab that is common to all file types. Select that tab now.

15.2 GRID LOADING OPTIONS

Before loading a grid, it is important that you review and understand the available options that determine how the data are loaded and/or interpreted.

Files Options	
Use existing RSGRID file settings	Optimization
Update RSGRID file with these settings	Keep original grid
Oreate a new RSGRID file	Oreate corner point grid - Shift *
	Create corner point grid - Avg *
	Node sharing:
	XY Tolerance: 0.050
	Z Tolerance: 0.050
	* Best performance / Least RAM

Grid Optimization

The Optimization options can be used to control how the grid will look, reduce the amount of RAM needed to load the grid, and improve performance when loading and viewing the data. There are three optimization options: Keep original grid, Create corner point – Shift, and Create Corner Point – Average.

In the grid file, the reservoir is modeled as thousands or even millions of individual cells. These cells are shaped like bricks, so eight individual points or nodes (with X-Y-Z coordinates) are required for each brick:



If two cells are adjacent and the nodes match, Tecplot RS will always "share" the nodes so that fewer points are needed. In this example, two bricks require 12 nodes instead of 16:



If the nodes aren't coincident, then all 16 points will be required:



Tecplot RS gives you two options for creating corner point grids from these "stepped" block models. By doing so, you smooth out the surface and force the sharing of nodes. This will greatly reduce the number of points required to store and display the model, and also give a more realistic look to the model.



The **Shift** option simply joins the corner of one cell to the adjacent node in the next highernumbered plane. The **Average** option, on the other hand, calculates a new node whose Z value is the average of the nodes being joined, and both corners are moved to this new location.

If NNCs (Non-Neighbor Connections) exist in the grid, the grid will NOT be smoothed across the NNC plane. In effect, NNCs define fault lines. NNCs are specific to Eclipse/SLB files, but other file formats have similar means of defining faults that will also be honored.

Tolerances

If you elect the "Keep original grid" option, the program will not force the smoothing. However, it will still try to save resources by sharing nodes that are duplicates (or nearly so).

You can enter a tolerance that defines how close the node coordinates must be in order to be considered the same. Different tolerances may be entered for horizontal (XY) and vertical (Z) dimensions. Tolerances may be very small, but don't use 0 (zero) because this pretty much guarantees that coordinates will never match. That's because there is always a small error due to the inability of a computer to exactly represent a floating-point value.

In general, a value of .05 (less than an inch) will deal with machine accuracy errors. If you encounter files where no smoothing is being performed even though the coordinates seem to match, you can try larger values. If you *want* to force more nodes to be smoothed, you can make the tolerance larger.

The RSGRID file

The options for grid optimization are very important the very first time you load grid data into Tecplot RS. That's because RS does the smoothing or node sharing and then saves the results into a new file with an extension of .rsgrid. The optimization can be a lengthy process, so we don't want to repeat it every time the file is loaded. The first load may take a longer time while the RSGRID file is created, but subsequent loads will be much faster.

The first three radio buttons on the Options tab are needed when you already have an rsgrid file but want to change the optimization options. They work like this:

Use existing RSGRID file settings	Creates a new file only if the RSGRID file is older than the simulator file that it was originally created from. In that case, the optimization settings used will be those that were in effect when the old file was originally created (the ones in the dialog are ignored).
Update RSGIRD file with these settings	Creates a new file if the optimization options in the dialog are different than those used when creating the existing RSGRID file. If the RSGRID file is older than the source file, the new one will use the dialog settings.
Create a new RSGRID file	Forces creation of a new RSGRID file using the settings in the dialog, no matter what.

You can also create the RSGRID file outside the Tecplot RS environment. A small executable program named **rspreprocess.exe** has been provided to allow you to do this. It can even be automatically launched at the end of a simulator run. See Appendix H in the RS User's Manual for more information.

15.3 LOADING THE GRID

For this exercise you're going to load two grid files. Both will be found in the installation folder (on Windows this is usually C:\Program Files\Tecplot\TecRS 2024 R1) under a sub-folder named 'examples'.

If you haven't yet done so, start by loading the Chelan.grid file. The Solution Data files should be filled in for you automatically. You can leave the Options selections at their default settings, and the Streamlines and Survey Wells fields should be blank. The **Make active** toggle should be checked. Click **OK** to load the file.

🚺 Load Grid D	ata 💽
C:/Program	Files/Tecplot/TecRS 20xx Rx/examples/chelan.grid
<u>I</u> nit file <u>R</u> estart file <u>X</u> Y file	C:/Program Files/Tecplot/TecRS 20xx Rx/examples/chelan.init C:/Program Files/Tecplot/TecRS 20xx Rx/examples/chelan.unrst C:/Program Files/Tecplot/TecRS 20xx Rx/examples/chelan.unst
Display name Streamlines Sur <u>v</u> ey wells	chelan
-	OK Cancel Help

15.4 LOADING MULTIPLE GRID FILES

Tecplot RS will let you load up to ten different grid files at once, and you can quickly flip back and forth between them or plot them side-by-side for comparison purposes.

Now that the Chelan file is loaded, you'll repeat the process and choose a second file. This time choose the quinaultlgr.grid file from the same folder. When the Load Grid Data dialog comes up, notice that the **Make active** toggle will be turned off by default. As with XY files, you can load multiple grids but only one will be designated the active file. The program assumes that all files after the first are inactive, but you can change it with this toggle. For now, leave all controls in their default state and press OK to load the new grid.

The Manage Data dialog

You can also change the active grid using the Manage Data dialog, accessed from either the toolbar or under the Project menu. This dialog also lets you:

- View information about your loaded files.
- Choose a different active data set.
- Designate a display name, which is usually a shorter name to identify the data set.
- Unload one or more loaded data sets.

Launch this dialog, choose the Grid tab, and highlight each of the Available Data Sets in turn. As you do, information about the highlighted file will be displayed at the top.



To change to a different active data set, simply highlight the file name in the lower list box. When you press **OK** and choose the desired plot type, the plot shown and sidebar lists will reflect the data from the newly active grid. For this tutorial, make sure that Chelan is highlighted before exiting the Manage Data dialog.

Since grid files can often take up large amounts of system RAM, when a grid is no longer needed it is a good idea to unload it. This releases the system memory in preparation for loading another file. The Unload tab can be used to unload selected files.

15.5 SAVE A PROJECT FILE

Now that you have grid data loaded, be sure to save the Project File. This will save you many steps when you want to use these data again. If you already have the Chelan project file open, simply clicking the Save button will add the newly loaded grid files. If you don't have a current project, clicking the Save button will bring up a dialog asking you to assign a name to the file.

Project Files are one of the best time savers available in Tecplot RS. Use them to quickly return to where you were last working.

CHAPTER 16: BASIC GRID PLOTS

In order to create the example plots shown in this chapter, make sure you have the chelan.grid file loaded and active. This can be found in the **examples** folder under your installation directory.

You will also want to open the Multi-Frame Options dialog and set the Frame Mode to **Single Frame.**

16.1 SELECTING THE GRID PLOT TYPE

If the grid file is the first file you open after starting Tecplot RS, the program will default to the 2D Grid plot type. If you were previously working in another plot type, however, this automatic switch will not happen.

In either case, you can select the type of grid display (2D or 3D) under the **Plot Type** heading on the menu, or using the small option menu at the bottom of the sidebar.

The 2D Grid plot displays one plane (layer) of grid cells at a time. You can choose which planes to plot by specifying both the view (I, J, or K) and the plane index. Radial grids also have the option of displaying the developed views at constant R or Theta values.

3D Grid plots show the entire reservoir grid in a 3-dimensional orthogonal or perspective view. The initial orientation of the view is preset, but the view is easily rotated, zoomed, or translated interactively.

16.2 GRID SIDEBARS

A different sidebar is displayed for the 2D and 3D Grid plot types, but both share some common controls. In this section we'll cover the selections and operations that are common to both 2D and 3D plots.

2D Grid 🗗	× 3D Grid & ×
Mach Dearthug	Mesh Inactive
V Contour V Wells	- V Shade Bubbles
Shade 📃 Bubbles 🖂	Uidbt I Stamp Plots
🗸 Light 🔤 🔲 Cell Labels 📼	
Translucency NNCs .	Iranslucency Cell Labels
2D plane in 3D view	Probe cell or well through Statistics plots
- Probe cell or well through Statistics plots	Histogram
	Depth Cross plot
Histogram	Well path 📼
Depth Cross plot	
	Properties
Properties	ORELPERM OWG
ORELPERM 🖉 OWG 🖸	SGAS
PRESSURE Delta	SOTI
SGAS	SWAT
	WRELPERM
SWAI	CDEPTH RMap
Grid Options	GROSS Grid Ontions
GROSS	PERMX
DERMY	PERMZ T
DERM7	
POROS	Times
ТДЕРТН	1 Jan 1970
TRANX	
TDANIV	
Times	Inside Views
1 Jan 197	0 [JK Slice 👻] 🔲 Show
🔺 📣 🕪 🕨 📰 📖	Ghost
	Auto-Update Apply
	Grid: GLOBAL
View Plane K - XY Axes	
1 No LGRs	
LGR	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10
	Clear All
Data Set	Data Set
Compare Delta Options	Compare Delta Options
2D Grid 🗸 🗸) [3D Grid 🔹 🥑

16.3 CHANGING THE VIEW (ROTATE, TRANSLATE, AND ZOOM)

You're going to start by examining some of the options for adjusting the view. If you aren't there already, please select **Plot Type > 2D Grid**. By default, the first K plane should be shown:



Zooming In/Out

Tecplot RS establishes the initial view so that the values on the X and Y axis should encompass the entire grid. There may be times that you would like to change that, perhaps because you'd like to take a closer look at a particular area.

Using the mouse, position the pointer anywhere on the frame. Click and *hold down* the middle mouse button, then move the mouse up and down. If you have only a two-button mouse with no middle mouse button, you can instead use [Ctrl] plus the right mouse button. Notice how the grid moves away from you as you move the mouse up, and closer when the mouse is moved down. Release the mouse button when you are satisfied with the view.

Another zoom tool can be found on the tool bar. With this, you can click and drag to create a rectangle around the desired view area.

Panning

The mouse can also be used to "shift" the view within the frame. This time, use the right mouse button. Click anywhere on the frame and hold down the button while dragging the view left, right, up, or down.

Alternatively, you can change to pan mode by clicking on the button shown here.

Adjusting the 3D View

These same controls will work on the 3D grid view. Select **Plot Type > 3D Grid**. Your initial display should appear:



As you did in the 2D view, use the middle mouse button to zoom in and out, or the right mouse button to pan up/down/left/right.

Rotating the 3D View

There are several options for rotating the 3D view. Start by clicking on the tool bar button pictured here. You can now press and hold the left mouse button, and as you drag the pointer your plot will rotate the view about the vertical (Z) axis.

While in this mode, press X or Y on your keyboard to change the axis of rotation to the X-axis or Y-axis, respectively.

Another rotation option uses a **trackball** approach, where the plot can be rotated freely about all axes. You can access trackball rotation in two ways. The first option is to click on the tool bar button shown here. Then, use the left mouse button to "roll" the ball in any direction. Alternatively, you can hold down the [Ctrl] key while pressing the *right* mouse button, and accomplish the same thing.

Reset View

Any time you'd like to start over when setting the view, press the Reset View button. This will return the plot (both 2D and 3D) to the initial default settings.

Note that in 2D views, the view is also reset any time you change the view plane (e.g. from I to J plane views).

View Presets

When 3D views are displayed, there are additional preset rotations available to you. Choose **View > View Presets** from the menu to choose from 8 standard orthographic projections plus a plan (aerial) view.

Paper Zoom

The view zoom options change how the data appears within the plot frame. You can also zoom in on the paper view, which is often helpful to read small text or see greater detail without modifying the plot itself. To do this, use the [Shift] key along with the middle or right mouse buttons as described for zooming and panning.

16.4 SELECTING VARIABLES

The variables contained in the solution files are presented in a single-select list box near the top of the sidebar. Timedependent (restart) variables are listed first, followed by static (init) values. Names are sorted alphabetically within each group. When the dialog is first initialized, the first variable in the list is highlighted by default. Each cell in the grid plot will be filled with a color representing the value of that variable at a given time.

Variables	
	-
ORELPERM	
PRESSURE	=
SGAS	-
SOIL	
SWAT	
WRELPERM	-

Note that the legend in the corner of the frame also shows the possible range of variable values and the colors associated with each.

On your system, try selecting several variables in turn and observe how the colors and legend changes for each.



16.5 SELECTING TIMES



Beneath the list of variables is a small slider control. This is used to choose the time step for time-dependent variables. Note that if the active file does not contain time-dependent variables

then this control will be disabled.

Start by selecting a time-dependent variable such as pressure or oil saturation (SOIL). Then use the mouse to drag the slider to a different position. When you release the mouse button the plot will be updated to reflect the values at the new time. As you move the slider, the time or date will also be displayed in the text field, allowing you to zero in on the date of interest.

The time can also be labeled on the plot, although this requires that the paper layout template include either the RS_PLOTTITLE or RS_ENTITY dynamic text. See Chapter 2 for details on the paper layout template.

Stepping Through Times

The slider is handy for quickly jumping to a particular time, but other options exist that give you a little more precise control. The small buttons beneath the slider look and act much like controls on a DVD player. Position the slider on the far left (first time step) and then click on the "Next" button [>] a couple of times. This will display each time step in turn. Press the "Previous" button [<] to back up a step.

Animating the Time Sequence

You can also automate the entire sequence of time steps. Start by selecting the first time step and then press the Play button. The program will cycle quickly through the entire range of time values. You can also animate backwards.

While the sequence is being animated, the "Stop" button will become active, and you can press it to interrupt the animation sequence.

Controlling Animation Speed

Sometimes the animation sequence goes by too quickly, especially when the grid is relatively small. You can control this using a selection in the Plot Options dialog.

Plot Options may be accessed using either the menu (**Options > Plot Options**) or the button on the tool bar. Either method will bring up a tabbed dialog. Select the first tab, which is labeled Load/Save:

Plot Options							-X -
Load / Save Varia	ables XY Lines	XY Axes	Grids	Grid Legend	Grid Axes	Cell Labels	Wells
Current Style: Fact Load at startup Load Save Save Save Reset Defaults	ory defaults Misc Settings Default time variab Date <u>f</u> ormat 2000 Ti <u>m</u> e format 40.7	le ○ <u>T</u> ime					
		Short					Long

A slider labeled "Animation Step Delay" controls the pause between each animated time step. Move it to the right to increase the delay and slow down the animation.

16.6 VARIABLE DISPLAY TOGGLES

Variables			
		OWG	(····)
ORELPERM		Delta	
PRESSURE	=		
SGAS		KSum	
SOIL		KAvg	(····)
SWAT		<u> </u>	
WRELPERM	-	Grid Opti	ons

Next to the list of variable names will be two or more toggles. When in 2D Grid mode, only the first two items will be listed, while the sidebar for 3D Grid views will include all four. These selections let you perform specialized computations on the variable values and show the results in the contour display.

The four options – OWG, Delta, KSum, and KAvg – are mutually exclusive. Selecting one will unselect any other. The individual toggles may be disabled if the active grid does not have the data needed to support that function.

OWG (Oil / Water / Gas) Saturation Plots

This control will be active only if your data set includes values for oil, water, and gas saturations. Note that if any two of these exist in the file, Tecplot RS will automatically compute the third for you.

Check the OWG toggle and note how the plot changes to a ternary RGB (Red/Green/Blue) color scheme. The intensity of each color is determined by the associated saturation variable: Blue = Water, Red = Gas, and Green = Oil. The legend also changes to the RGB color triangle.



You can change the time steps or animate the plot to see how the relative oil, gas, and water saturations change over time. For example, by observing the predominantly blue regions you can easily monitor areas with high water saturations.

The Delta Toggle

Instead of showing the variable value at each time step, you may create plots that represent the change in values over time relative to a reference time step (usually the first, but you can select any reference time step using the [...] button). This is accomplished using the Delta toggle.

When the delta option is turned on, the colors in each cell represent the difference in values at the current time and reference time. If the slider is at the first time step AND your reference time step is step #1 (the default), then the entire grid should be a solid color representing a value of zero, and as you move to later times the colors will show how the variable value increases or decreases over time.



The delta toggle will be turned off and disabled when no time-dependent variables exist in the file. Try turning on the Delta option with the sample data. Make sure you have a time-dependent variable selected, choose a time step other than the first, and note the changes on your display.

Note that this toggle controls *time* deltas within a single grid and between two different times. There is another delta toggle at the bottom of the sidebar that controls *grid* delta values between two different data sets.

K Sum and K Avg (3D plots only)

When activated, the K Sum toggle will cause Tecplot RS to sum all the variable values in a column (all cells with matching I and J indices). The summed value is displayed in all cells of that column. Since these data are typically viewed from the top, the program will switch to a plan view, but the full 3D grid still exists and can be seen using the Reset View button or the view presets under the View menu.

Cells in LGRs are summed separately from the parent grids, and if the LGR is not at the grid surface you will need to switch back to an orthographic projection in order to see it.

When K Avg is selected, the summed values are divided by the number of cells in that column. PLEASE NOTE that this is NOT a volume-weighted option.

K Sum and K Average will limit calculations to visible cells - those not turned off by blanking or Inside View settings. Blanking and Inside Views are covered in later chapters.

16.7 SELECTING 2D PLANES

If you are viewing a 3D grid right now, please switch to the 2D view.

When you switched to the 2D view the program defaulted to display the plane at K=1. You're not limited to this view – the controls in the middle of the 2D Grid sidebar let you choose both the view direction and the plane number.



The View Plane options let you choose to look at planes in any of the three dimensions: I, J, or K. When you make this selection, the list box on the left will be updated to include the plane numbers available in that dimension. The highlighted number indicates the index being viewed. You may choose another plane by clicking on the desired number, or the [<] and [>] buttons can be used to scroll up and down the list. When the list control has focus, the arrow keys on your keyboard can also be used.

For this exercise, look at several different planes in each of the three views (I, J, and K). Try changing the variable and/or animating time steps.



The LGR controls (to the right of the plane list box) are activated when your file has local grid refinements. You'll learn how to use these in a later exercise.

16.8 WELLS TOGGLE

Inactive	
🔽 Wells	
Bubbles	
🔲 Cell Labels	
NNCs	

On the top of the sidebar are several toggles that control additional items that can be displayed on your grid plot. Start by placing the time slider to the middle of the scale, then turn on the Wells toggle to show the well geometries for the reservoir.

In 2D Grid plots, a

well is usually displayed only if it has a completion in the current plane. As you step through the available planes, you may see wells appear and disappear accordingly.

[....]

(····)

......

(····)





In the I planes, for example, you won't see a well until you hit plane #8!

Switch back to a 3D Grid plot type to view the wells in 3 dimensions:



Wells change over time. If you don't see any on your plot, it may be because your slider is at the initial time step and no wells are on line at that time. Try advancing the times and see how things change. In the example Chelan file, you may see 0, 2, 3, 4, or 5 wells depending on the selected time.

A symbol is drawn at the top of each well, and varying shapes and colors are used to differentiate well types; producer, gas injector, water injector, etc. Other symbols are shown at each well node or completion, although they may be hidden on the 3D view.

Using Zone Layers and Zone Effects to View the Grid Interior

To view the hidden completion nodes, turn on the Translucency toggle on the sidebar menu. The surface should change so that you can see through to the previously hidden details beneath.

	Mesh
V	Contour
1	Connect
1	Shade
1	Light
V	Translucency

You may also want to turn off the Mesh layer and/or rotate the view to make the wells easier to see. Finally, turning on the Light option will highlight the surface details that were lost when the mesh was turned off.



Changing Well Styles

You have extensive control over how wells are drawn and labeled in Tecplot RS. These options are found on the Wells tab in Plot Options.

Load / Save	Variables	XY Lines	XY Axes	Grids	Grid Legend	Grid Axes	Cell Labels	Wells
Symbols				-Labels -				
Type	Producer		•	Shov	v			
<u>S</u> hape	Sphere		•	Eont H	lelvetica Bold	Siz <u>e</u> 2.00)	
<u>C</u> olor	Black		•	Color G	ray	<u>U</u> nits Fran	ne (%)	•
Size	2.20		%	Connect	Nodes			
<u>O</u> ffset	10			Color	Black	▼ Wi <u>d</u>	th 0.4	*
Measured as	:							
% offset from well head			-In 2D vie	ws, show:				
% offset fro	om grid max	a d		© <u>A</u> ll w	ells with connecti	vity		
Fixed offset	t from grid m	ax		Wells	s with completion	s in current pla	ine	
			Com	pletion <u>n</u> odes onl	у			
Apply								

The simulator output generally includes a type for each well. The Chelan data set contains two types – producer and gas injector. In addition, Tecplot RS also reads the well status and knows when a well is closed down or shut in. Finally, the individual completions will also have two states – open or closed. In 2D and 3D grid views, symbols will be drawn at the well head and completion nodes that will help identify each type and state. Since states may change over time, the symbols will be updated to reflect the changing status as you move the slider.

You may designate the shape, color, and size for each of these symbols. For this exercise, we're going to select a different symbol for completions, enlarge the text so it's easier to read, and adjust the placement of the well head with respect to the grid surface.

Note that the current symbol type is Producer, and the other options show that wells of this type will be shown as a black sphere that is drawn at a size that is 2.2% of the frame size.

Symbols	
<u>T</u> ype	Open Node 🔹
<u>S</u> hape	Square
<u>C</u> olor	White
Size	0.80 %

Change the Type to **Open Node**. The shape, color, and size should show circle, white, and 0.8%, reflecting the options for drawing the symbols at open completion nodes. Use the option menu to change the shape to **Square**. You'll then need to click on the **Apply** button to see your changes on the plot.

Feel free to change some of the other options and see the effects of your changes. Remember that not all the wells exist in the Chelan data set at earlier times, so you may need to push the time slider to at least the middle of the range.

Next, let's change the size of the well labels to make them a bit easier to read. The default size is 2.0, again representing a percentage of the frame height. Change this to 2.2 and again click on **Apply** to see the

Labels							
Show							
<u>F</u> ont	Helvetica Bold	•	Siz <u>e</u>	2.2			
Color	Gray	•	<u>U</u> nits	Frame (%) 🔹			

differences. You can also alter the color and font.

Finally, we'll learn how to control the placement of the well type symbol. The well type symbol is drawn above the surface of the grid in order to make it visible. There are four different ways for computing the offset:

- 1. % offset from well head (actually the first node in the well geometry)
- 2. % offset from grid max (the highest elevation in the grid geometry)
- 3. Fixed offset from well head
- 4. Fixed offset from grid max

Generally the first two options are better defaults since they will adapt nicely for different grids. The default is option #2, which ensures that the well type symbols are always placed at the same elevation, and that elevation will be somewhat higher than the highest point on the surface.

For this exercise, change to the option "% offset from well head", and change the offset value to 20. After clicking on **Apply** you'll see that the well type symbols more closely follow the surface of the grid.



Again, feel free to experiment with all the options on the Wells tab to see how they affect your plot. You may also want to save one or more gallery plots as you work.

More Wells...

A small [...] button next to the Wells toggle gives you additional control over the well display. Press it to bring up this dialog.

With the options presented here, you can limit the displayed wells to a subset of those in the file. This is often helpful when there are so many wells in the reservoir that displaying all of them makes it difficult to see the details.

💟 Wells	×				
Show Wells	<u>Styles</u>				
Well 🕂	Select All				
OIL-01 OIL-02	Make SS				
OIL-03 OIL-04	SS001				
GAS-05	Edit SS				
Refresh					
Sel Sets Mous	e				
Apply					
Add to selection	ns				
Remove from selections					
Replace selection	ions				
[Close Help				

By default, all your wells will be selected for display. Simply change the highlights in the list box to choose a subset of the available wells for display. Use **Refresh** to apply your changes to the current plot.

Of course, if you have thousands of wells, choosing the ones you want to display from a list box is not terribly efficient. That's where the additional controls come in. Here we have Selection Sets again!

If you haven't done so already, you should read chapters 4 and 5, which cover the basic concept of selection sets and how to create them using Filters.

Within this dialog, you can both create new selection sets from the list of highlighted wells, AND you can use existing selection sets to change those highlights.

To create a new selection set (SS), start by highlighting the wells you want to include in the upper list box. Assign a name for the set (or use the supplied default) and click on **Make SS**.

To use an existing SS to alter the highlights, select the set you want from the lower list box. Choose the rule for making the changes:

- Add to selections Each well name from the selection set will be highlighted in the upper list box, without disturbing existing selections.
- **Remove from selections** Each well name from the selection set will be turned off in the upper list box, without disturbing other selections.
- **Replace selections** All highlights in the upper list will be modified so that only the wells in the selection set will be highlighted.

Press **Apply** to use the selection set to alter the wells selected for display.

You can also use the mouse to change the list highlights. To do this, start by turning on the well display **with the well labels** (labels are controlled in Plot Options). This is necessary because you will be selecting the well labels with the mouse, rather than the well symbols. If you like you can make the labels very small.

Make sure the Mouse tab is active on the dialog. Use the mouse to pick the wells. You can do this by rubber-banding a box around the ones you want, and also by holding down [Shift] and clicking

Sel Sets	Mouse						
Use the mouse to pick or highlight the well name LABELS on the grid plot. Choose the desired add, remove, or replace option, then click [Apply].							
Apply							
Add to selections							
<u>Remove</u> from selections							
Replace selections							

on individual labels. Just remember it is the labels (text) you want; any other picks will be ignored.

Press Apply to use the picked wells to alter the well highlights.

Save Your Project File

Hitting the Save button will ensure that the Selection Sets that you just created plus your style changes will be saved in your current Project File.

16.9 MORE OPTIONS

There are dozens of different options for changing the way grid plots are displayed. Here are some things you should try with 3D Grid views so that you can see the possibilities:

- On the Plot Options: Wells tab, try both the **Frame Units** and **Grid Units** settings for text (note that you will have to click on the **Apply** button to see the effects). Each time, zoom in and out on the grid view and watch what happens to the well labels.
- In the Plot Options: Grid Axes tab, turn on the toggle for **Show 3D Axes**.
- In the Plot Options: Grids tab, switch the Contour Type to **Continuous Flood**. Look at several variables and time steps in both 2D and 3D Grid types, comparing them to the results you had when **Cell Center Flood** was selected.
- With wells displayed, turn on and off the sidebar toggles for Mesh, Contour, Connect, Lighting, and Translucency.
- In the Grid Options dialog, set the **3D Z-Axis Scale** to 2. View the results, then try it again using a scale of 0 (zero).

CHAPTER 17: MULTI-FRAME GRID PLOTS

Up to now, all the grid examples have utilized a single frame. In this exercise you will learn how to create a page containing multiple grid plots.

17.1 THE MULTI-FRAME OPTIONS DIALOG

🚺 Multi-Frame Options 🛛 🔀							
Frame Mode:							
○ Single Frame							
Multi-Frames							
Columns 2	-						
Rows 2	*						
Link Grid View / Rotation							
Link Inside Views / Blanking							
Link Layer Toggles							
✓ Link <u>W</u> ell Toggle							
Frame Spacing							
2 A of Paper Size							
Quick Plots							
Location <u>A</u> rea (%)							
○ <u>B</u> ottom of Page 30	-						
Right Side of Page							
Close Apply Help							

If you worked through the chapters on XY plots, you should already be familiar with the multi-frame options. However, there are a few new things to learn when creating multi-frames with grid data.

To bring up the dialog that controls the multiframe options, choose **Options > Multi-Frame Options** from the RS Manager menu, or press the button on the sidebar. This will bring up the following dialog:

Change the Frame Mode to Multi, as shown here. Make sure the other settings are also as shown, and then select **Close**.

17.2 DISPLAYING MULTIPLE GRID VIEWS

If you have loaded the Chelan data set, the 2D Grid views for K plane 1 will look something like this.



You should have a total of four frames (two rows by two columns). All frames will contain the same view and plane number, but a different variable will be displayed in each.

Try changing the time step, view plane, and plane number. You'll see all four frames update simultaneously.

17.3 CHANGING VARIABLES IN MULTI-FRAME VIEWS

Your initial multi-frame grid plot will put the currently selected variable in the first frame, and each subsequent frame will display the next variable in the list. This is a useful default, but is easily changed.

To select a new variable for a specific frame, first make the frame active by clicking anywhere within it. Then, choose the variable to be shown in that frame from the sidebar. The affected frame should be instantly updated to reflect the new values. You can do this for each frame in turn.

17.4 FRAME LINKING

- Link Grid View / Rotation
- Link Inside Views / Blanking
- Link Layer Toggles
- Link Well Toggle

You can control whether a change made to one frame will be made just in that frame or in all frames of a multi-frame plot. The choices are made using the toggles in the Multi-Frame dialog.

Link Grid View / Rotation

While multiple frames are displayed, use any of the techniques you learned in section 15.3 to change the view in one of the frames. You may rotate a 3D view, zoom in, or translate.

Right now, you any change made to one frame is made in all the others simultaneously. This happens because the Link Grid Views toggle in the Multi-Frames dialog was turned on. This setting instructs Tecplot RS to make sure all frames have matching views. You can return to the Multi-Frames dialog and turn off the toggle. When view linking is off, you can click on each frame in turn and set a different view:



Link Layer Toggles

Layer Toggles include the Mesh, Contour, Connect (which turns on/off the lines connecting well nodes), Shade, Translucency, and Light options at the top of the grid sidebars, and the Lines and Symbols toggles in the XY plot sidebars. When linked, any change to these toggles will affect all frames. Turn off the link to set these options independently for each frame.

Link Well Toggle

When turned off, well geometries in grid plots will be displayed only in the first frame. When on, wells will be displayed in all frames. Unlike the layer toggles, well display cannot change from frame to frame. This option simply lets you control whether wells are shown in one frame or all.

Link Inside Views / Blanking

Inside Views and Value Blanking are ways to view and explore the interior of your grid model. These are covered in Chapter 18. This option in the Mutli-Frame Options dialog control whether those views are shown in only the first frame or in all frames.

17.5 SPECIAL PURPOSE MULTI-FRAME PLOTS

Tecplot RS also has two other 'special purpose' multi-frame grid plots.

Dual Porosity Views

Some grid models contain dual-porosity data, which have two sets of solution variables for a single grid model - one set for the matrix grid and another set for fracture values. Using the Grid Options dialog (accessible from a button on the side bar), you can choose to display the values for either the fracture or matrix.

Crid Options							x
Orient/Thicken Inactive Cells		Dual Poros	Translate	Rotate	Scale		
Grid Display		-Well I	Display				
Show Matrix	Show Matrix Grid		Show wells only when completed in the displayed grid				
Show Fractur	Show Fracture Grid		Show wells regardless of matrix/fracture match				
Show Both *	Show <u>B</u> oth *						
*Showing both g display two fram overrides selection the multi-frame d	rids will es and ons in lialog.						
Apply							
					Close	Help	

You can also choose a "Both" view. In this case, the selections in the Multi-Frame Options dialog are overridden, and RS will display two frames - one for matrix and one for fracture values.

All selections for variables, styles, and display options are also linked, again overriding the toggles in the Multi-Frames dialog.

This option is available only when the active grid contains dual porosity data.

Side-By-Side Grid Comparisons

Tecplot RS also allows you to create side-by-side frames that will compare two or more data sets. This feature is covered in chapter 20. For these plots, the number of frames is dependent on the number of data sets selected for comparison, ignoring the rows/columns selections in the Multi-Frame dialog.

CHAPTER 18: ADVANCED GRID PLOTS

In preparation for the exercises in this chapter you will use the quinaultlgr data set. If you are using the project file created in Chapter 14, the file is already loaded and you simply need to set it as the active data set using the Manage Data dialog.

If you neglected to create a project file, simply repeat the steps in Chapter 14 and create it now. However, this time be sure to make quinaultigr the active data set.

- 1. After loading/selecting the grid file, select Plot Type > 2D Grid.
- 2. Open the multi-frame dialog, and:
 - Select Multi frames
 - Choose 2 columns and 1 row
 - Turn ON both the view and value blanking linking toggles
- 3. Set the View Plane to K XY Axes
- 4. Highlight plane 1 in the plane number dialogs.
- 5. Click on each frame and select SOIL (Oil Saturation) as the variable. (You'll need to do this for both frames).
- 6. Advance the time slider to the approximate middle of the scale.
- 7. Click on the Grid Options button and make sure your settings look like this, then close the dialog:


At this point your screen should look something like this:



You're ready to begin.



You now have 2 views of the same plane – one viewed "head on", and the other in 3D! If your 3D view is cut off on the edges, use the middle mouse button to zoom out a little.

Planes View Plane K - X	Ү Ах	es	•
1 2 3		B_INJ 1 2 3 4 5 6	LGR
41	Þ	-	i>

In the first list box with plane numbers, select plane #2 either by highlighting it or by pressing the Next button.

With the Quick 3D view, it's easy to see where the selected plane falls in the grid area. Select each K plane in turn and watch how things change in the sidebar and on the plot.



NOTE

The last frame of a multi-frame view always becomes the Quick 3D frame, no matter how many plot frames are shown. If you are in single-frame mode, then your current 2D view will be switched to 3D. It will switch back to 2D mode when you turn off the Quick 3D toggle.

18.2 LGRs

Our sample grid contains LGRs (Local Grid Refinements), and as you stepped through the planes you may have noticed that the second list box and LGR drop-list options changed when you made selections in the first.

The planes selected in the larger list box are those of the global grid. If the selected plane intersects an LGR, then the other controls will reflect which LGRs are intersected and which planes are available in those LGRs.

For example, start by selecting K plane #1. Then click on the drop-down list on the right to expand it.

The LGR drop list now shows three LGR names: B_INJ, C_INJ, and B_PROD. These are all the LGRs that are intersected by K plane 1.



C_INJ is slightly indented under B_INJ. This indicates

that C_INJ is a sub-grid of B_INJ. In other words, C_INJ is a child grid and B_INJ is the parent. B_INJ and B_PROD are both children of the parent global grid.

If needed, choose the B_INJ option and notice that the second list box contains numbers from 1 to 6, indicating that the B_INJ LGR contains six K planes. Plane #1 is highlighted, so this is the one that appears on the plot.



Change the highlight in the smaller list box to "2", and note how your plot changes:

The changes in the 2D view are subtle, but in the Quick 3D view it's easy to see that we are viewing a different plane in the LGR. You can also see how the planes from the main grid line up with the LGR plane.

If you choose plane 2 in the larger list box, the LGR plane will sync to plane 3. Choosing plane 3 in the global grid will show plane 5 in the LGR, although you can again choose a different LGR plane.

Selections made to the parent grid will always choose the closest plane in the child. By default, the child LGR planes can be selected independently of the parent. However, you can change this using the "Lock" button.

Click on the lock button to engage it, then select successive planes in the child grid. You'll notice that the parent grid plane now follows the selections in the child.

NOTE

Using these controls you can view any 2D plane in any I, J, or K orientation. The Quick 3D view is not required, but can be helpful to determine spatial relationships, especially when there are LGRs.

18.3 INSIDE VIEWS

The Quick 3D view effectively shows a slice of your model in 3D space. However, the primary purpose of Quick 3D is to make it easier to identify which 2D plane you are viewing, especially when LGRs are involved. However, there are many additional tools for looking 'inside' your grid.



For this exercise, first return to the Multi-Frame options and switch the Frame Mode back to Single Frame. After closing that dialog, change the Plot Type to 3D Grid.

IJK Slices

Inside	liews		
IJK Slic	e 🔹	Show	
		Ghost	
🗸 Aut	o-Update	Apply	
Grid:	GLOBAL -		
Plane:	• I	1	
		2	
		3	
		4	-
		5	=
		6	
		7	
		8	
	Clear All	9	Ψ.

The 3D Grid sidebar contains a group of controls labeled "Inside Views". Change the settings on your sidebar to match what is shown here, and also press the **Clear All** button. You'll notice some similarity to the controls you used in the previous exercise. There's an option list for choosing which grid/LGR, an option list for the plane (I, J, or K), and a list box with plane numbers that correspond to the selected grid and view plane. Your plot should show a translucent box that represents the grid boundary: Now do the following:

- 1. With Grid = GLOBAL, Plane = I, highlight planes 3 and 8 (HINT: Hold down the [Ctrl] key in order to select or unselect items in a list that are not consecutive).
- 2. Change to Grid = B_INJ, Plane = J and highlight plane 4.
- 3. Change to Grid = C_PROD, Plane = K, and highlight 3.

If the Auto-Update toggle was checked, you should have seen each plane appear as you selected it. If not, press the **Apply** button to see this plot:



With IJK Slices, you can choose any number of planes, in any direction, and for any grid/LGR. Unlike the 2D Grid view, the LGR planes displayed here are independent of the plane selected in the parent grid.

XYZ Slices

XYZ Slices give you another option for looking at the interior of your model. In this case, the slice position is determined purely by coordinate value, and no selection of plane number or LGR is needed.

Use the option menu to change the view type to XYZ Slice, then set your controls as shown here.

Experiment by moving the sliders around, selecting a different X/Y/Z direction, and changing the number of slices. You can also use sidebar controls to change the value shown or the time step.





Arbitrary Slices

Arbitrary slices give you yet another option for viewing slices through your model. In this mode you can define the endpoints of one or more vertical slices that can be oriented in any direction.

A common application for this would be to view a slice between wells. Since you choose the endpoints of the slice using the mouse, you can create slices through any two points.

Start by selecting the Arb Slice view type for Inside Views. For this exercise you should start with the



Show and Clip toggles turned off as shown here. You should also turn on the Wells display. If there are any items in the Slices list, highlight them and hit Delete. Your plot should look something like this:



To define the endpoints of a slice, click the Create button. The mouse pointer will turn into a crosshair as it does when probing. Click on two points on the surface of the grid in the approximate locations shown by the small + marks here:



The Slices list box will be updated to show "**P1-P2**", which is indicating a slice between two arbitrary points.

Now click the Create button a second time. This will instruct RS to start a new slice (instead of continuing from the last clicked point). Hold down the [Ctrl] key and click on each of the two well head symbols. This time, the slice will be shown as "**INJ_11 – PROD_101**". By holding down the Ctrl button, you asked RS to snap to the nearest point, and when the nearest point is the well head, it will identify the points by the well names.

Turn on the Show toggle to display your slices. Changing the time and/or variable will also update the values on the slice. When you have multiple slices defined, you can also turn them on and off by using the list box to highlight only the ones you want to view and then pressing the Apply button.



Additional Inside Views

There are several more Inside View options that you can use to explore the interior of your model:

- IJK Blank Similar to IJK Slicing, but instead of selecting individual slices you choose a range of planes in the I, J, and/or K directions.
- Well Blank View the cells containing well completions. Choose which wells you want to show.
- Iso Surfaces Create surfaces along a constant variable value, such as where water saturation is equal to .5.
- LGRs Turn on/off the display of LGRs so that each can be viewed independently.
- **Streamlines** Load and display streamline data output in the Frontsim format.
- **NNCs** Display Non-Neighbor Connection faces (Eclipse/SLB files only) and flood with special NNC variables.
- **Faults** Display cell faces along fault lines as defined by user input constraints, in the grid file, or NNC definitions.

18.4 GRID DATA EQUATIONS

Data equations are used to compute new variables from existing grid values. You can create a single new variable or several. New variables appear in the list and can be selected for contouring. If the new values are computed from time-dependent data, they will be updated as the time step changes.

Although equations can be much more complex than this, a basic equation might appear as:

... where *<operator>* includes (but is not limited to) standard operators such as +, -, /, and *. For example:

{RATIO} = {SWAT} / {SOIL}

The new variable is named "RATIO" and is defined as the ratio of water to oil saturation. Both new and existing variable names are always surrounded by curly brackets { }.

NOTE: If Tecplot RS detects that the variable used as the divisor has a range of values that include zero, it will not accept the equation because of the potential for divide by 0 errors.

You can also include constants in your calculations, such as:

$$\{SGAS\} = 1.0 - \{SOIL\} - \{SWAT\}$$

The capabilities of equations go far beyond these simple examples. A complete description of equations can be found in the appendix of the *Tecplot RS User's Manual*.

Although the instructions in the manual show the use of variable numbers to define equations (e.g., "V3" instead of "{SOIL}"), we recommend using explicit variable names for reservoir plots. This will help avoid errors and will also make your equations generic so that they can be used with different projects.

For this exercise, start by bringing up the dialog using either **Data > Grid Equations** from the RS top level menu or the button on the toolbar.

Start by double-clicking the [NEW] line at the top of the list. The entry field will then display:

{VARNAME1}=

You may edit the variable name to be something else, such as "MYVAR", and then make sure to move the cursor back to the end of the line. **{MYVAR} = {SOIL} * {GROSS}**

Grid Equations	ion or just start boing
[NEW] [MYVAR]={SOIL}*{GROSS}	Test
{MYVAR}={SOIL}*{GROSS}	Enter Cancel Variables - Double-click to insert into equation.
BEG BAK <-	PRESSURE SGAS SOIL SWAT CDEPTH GROSS PERMX
1 2 3 - () LOG LOGIO EXP 0 . , + { } MIN MAX IF	POROS TRANX MYVAR Close Help Save As

Be sure that you have curly braces around each variable name. For variables that already exist, the best way to do this is to select the variables by double-clicking on them in the list: it's not only faster, it prevents typos. You can use the mouse or keyboard to enter the multiplication symbol, *, and the assignment operator, =.

Press the Enter key on your keyboard or click the Enter button on the dialog to record the equation, which will put it in the list of variables at the top. Once there, the **Test** button can be used to make sure you have a valid equation.

Close the dialog, then look at the variable list in the sidebar. MYVAR should appear at the end of the list (you may need to scroll down). Select it and the plot will be contoured with the new values. Change the slider to see it updated for different times. You can use this variable as you would any other in the list.

Equations will be saved in your project file and will be automatically applied the next time you load the project. Equation variables always appear at the end of the variable list.

18.5 VALUE BLANKING

Value Blanking is a powerful tool that lets you turn on or off individual drawing elements (usually cells) according to the values of selected constraint variables.

The best way to understand value blanking is to see it in action. For this exercise, load the quinaultlgr.grid file and set the frame mode to Single Frame. Select the 3D Grid plot type, and make sure Inside Views are turned off. Choose the variable SOIL and move the time slider to the starting position.



The dialog shown below is accessed either by pressing the Value Blanking button on the toolbar, or by choosing **Data > Cell Blanking** from the menu. Make sure the Value tab is active.

💟 Cell Blanking 🛛 🕰
Value Pick
Include Value Blanking
Constraint
1 2 3 4 5 6
Active
Blank when
X
Is less than or equal to 🔹
© ⊻ariable
© <u>⊂</u> onstant
Υ -
Auto-Update Apply
Close Help

Start by turning on the toggle to "Include Value Blanking".

Next, change the settings for constraint #1 to those shown here.

With these settings, you are asking Tecplot RS to display only those grid cells that have an oil saturation in excess of 0.5.

Finally, press the Apply button.

There's no immediate change to your plot, because all the oil saturation values are greater than 0.5 at the first time step. However, advance the slider to about the middle of the range and your plot will look like this:



The oil saturation is decreasing in the corner where the injector well is located. When the saturation drops below the .5 limit, the cell is blanked.

It is not necessary to display the same variable that is used for the blanking criterion. Try changing the display variable to Pressure and then press [->] to animate the time sequence. Now you can watch the pressures change in cells where the oil saturation is high.

You can enter multiple constraints for value blanking, and you can also test against other variables as well as constants.

Value blanking can also be applied on 2D grids.

Value Blanking in Multi-Frame Plots

Remember that the Multi-Frame dialog also has a toggle related to value blanking: Link Inside Views / Blanking.

If left unchecked, value blanking and inside views are applied to only the first frame of a multi-frame plot.

If you want all your frames to show the same views, remember to turn on this toggle.

Multi-Fram	nes				
<u>C</u> olumns	2	* *			
<u>R</u> ows	2	*			
☑ Link <u>G</u> rid View / Rotation					
V Link Inside Views / Blanking					
☑ Link Layer Toggles					
Link Well Toggle					

Note that many Inside Views are simply specialized applications of blanking. Value Blanking, IJK Slices, IJK Blanking, and Well Blanking all make it possible to explore the interior of your grid model by blanking the cells you are not interested in seeing. Blanked cells are also useful when doing computations, as you'll see in the next exercises.

18.6 DATA INTEGRATION

You saw one kind of integration in section 15.6 when you used the KSum toggle to display the sum of values in a column of cells. Another option for integration can be found using the Integration dialog, which is accessed using either **Analyze > Integration** from the menu, or the button on the toolbar.

🚺 Integrat	tion											[? ×
Cell Sele	ction				Co	mputation Options							
Visib	Visible cells			V	Apply volume value			Bin results					
Cells	Cells containing open well nodes			Vol	Volume variable: GROSS 🔻			Bin variabl <u>e</u> :		TIME STEP		-	
Cells	Cells containing <u>any</u> well node (open or closed)			d)				Range:		1 to 9			
									Num	ber of bins	9		*
) Bin į	nterval	1		
Data set: (quinaultlg	r, Selectio	n: Visible c	ells, Time: 3	30 Dec 200	94, Integration valu	ue: SOIL, Volume	value:	GROSS				
	# Cells	Sum	Min	Max	Avg	Weighted Avg	Product Sum	Volu	me Sum	Product Mi	n Prod	uct Max	Product
All Cells	766	504.047	0.100039	0.772874	0.658025	0.690469	27287.3	39520)	1.33385	69.55	81	35.6232
•	1		1				1						4
C	ompute		Save	CSV file									
											Close		Help
											0.030		

This function will create a report showing values computed from the grid cells. For any given variable the program will display minimum and maximum values, the sum of all values, and the average for the selected cells.

The variable being calculated is selected on the sidebar – it is the same one that is currently displayed on the grid. The sidebar also controls the time at which values are computed for transient variables.

You can also apply a volume value. For example, if the GROSS value represents the cell volume, applying this will give you a second set of values for the product of SOIL * GROSS.

The cells used to compute these values can be limited according to the Value Blanking criteria. Visible Cells is the default criterion, meaning that the results will reflect only the cells that you can see on the screen.

For this exercise, try turning on and off the Value Blanking from the preceding exercise and note the difference in the number of cells and the totals for each. You can also try this while displaying Inside Views or 2D Grid plots. The latter is a way you might limit the calculations to only those cells in a single K plane, for example.

Another option is the ability to bin the results by another variable. For example, you can see how the cell depth affects the oil saturation:

💟 Integration									8	×	
Cell Selection											
• Visible <u>c</u> ells			[Apply volume value Bin results							
Cells containing open we	ell nodes		١	/olume va <u>r</u> i	able:	PRESSURE -	Bin variable	CDEP	тн	н 🔻	
Cells containing any well	l node (oj	oen or clos	sed)				Range:	8131.	67 to 8355		
							Number	of bins 5		* *	
							🔘 Bin inter	rval 1			
Data set: quinaultlgr, Selection	n: Visible (ells, Time	: 30 Dec 20	004, Integr	ation value	: SOIL, Volume val	ue: PRESSURE, E	inned by: CDEP	тн		
	# Cells	Sum	Min	Max	Avg	Weighted Avg	Product Sum	Volume Sum	Product Min	Prod	
CDEPTH <= 8150	100	36.9524	0.100039	0.772834	0.369524	0.367965	250663	681214	685.656	5247.5	
8150 < CDEPTH <= 8200	170	89.7685	0.160126	0.772855	0.52805	0.527281	610982	1.15874e+006	1098.04	5271.1	
8200 < CDEPTH <= 8250	198	148.682	0.21626	0.77287	0.750918	0.750781	1.01249e+006	1.34859e+006	1483.94	5295.5	
8250 < CDEPTH <= 8300	72	54.3836	0.237385	0.772872	0.755328	0.755237	371377	491735	1630.39	5302.9	
8300 < CDEPTH <= 8350	154	118.622	0.425734	0.772872	0.770271	0.770263	812788	1.05521e+006	2926.57	5312.9	
8350 < CDEPTH	72	55.6393	0.772099	0.772874	0.772769	0.772769	381216	493311	5219.45	5320 . €	
All Cells	766	504.047	0.100039	0.772874	0.658025	0.657803	3.43952e+006	5.2288e+006	685.656	5320.€	
•				· 						+	
Compute	Save	CSV file .									
								Clos	e He	lp	

18.7 QUICK PLOTS

Tecplot RS offers a variety of **quick plots**. Quick plots utilize one or more separate, smaller frames that 'borrow' some space from the main plot frames. The amount of space that will be occupied by the quick plots, and their position is determined by settings in the **Multi-Frame** dialog. For this exercise, set the options as shown here.



Histograms

Your first quick plot will be a histogram that shows the number and distribution of values in the grid plot. You can use either the button from the toolbar or the menu (**Analyze** > **Histogram**) to bring up this dialog (Note that you must be showing either a 2D or 3D grid plot in order to choose this option). You can also check the **Stats** toggle on the top of the sidebar.

Start by setting the options as shown here. On the main sidebar, choose the variable and time step that you would like to see. The histogram should update immediately to reflect your selections.

💟 Quick Stats	? 💌
Show	
Type: 🔘 <u>H</u> istog	gram
Cross	Plot
Limits	
All Cells	Visible Cells
Pipping	
Match Contol	urs
# <u>B</u> ins	20 😌
<u>R</u> ange	From data 🔻
✓ Nice Intervals	S
Display	
Stats	Basic 💌
Show Legend	I
	Close Help

For example, the histogram plot below shows oil saturation on the last time step of our sample file.



Try animating your plot over time. The histogram plot will animate along with the grid plot.

As with integrations, you can limit which cells are included in the histogram. Change the Limits option to **Visible Cells**, and change your grid plot to use either Value Blanking or one of the inside views that show whole cells (IJK Slices, IJK Blanking, or Well Blanking). Note that the title of the histogram frame indicates how many total cells were found.

The histogram dialog also gives you options for controlling the number of bins, the amount of data in the header, and how the data ranges are determined. Experiment with each of these to see how they impact the plot.

Time/history Cell Plots

The next quick plot you'll look at is accessed by checking the Time/history toggle on the sidebar. It is found just under the toggles for Mesh, Contour, etc.

You need to ensure that the variable selected for display is a transient (time-dependent) value. In the Quinault LGR sample data, the first

 Mesh Contour Shade Light Translucency 	Inactive ✓ Wells ✓ Bubbles Stamp Plots Cell Labels	
Probe cell or well through	Statistics plots	
Droportion		

four variables (plus the computed "MYVAR" values we calculated a few pages ago) are transient.

As soon as the Time/history toggle is checked your mouse pointer will change from an arrow to a crosshair. This is your cue to click on the cell for which you want a Time/history plot. Once chosen your plot should be immediately updated and should look something like this:



This plot shows the oil saturation values for a single cell over for time steps. If you change the variable or click a different cell, the Time/history frame updates to reflect the new selection.

CHAPTER 19: COMBO PLOTS

Combo Plots are those where grid plots can be combined with other data types. The combo data may include XY files from simulator or observed data files, RFT data, and streamline data files. In general, these data are in a file separate from the grid file and must be loaded independently. For this exercise, both the needed files (guinaultlgr.grid and quinaultlgr-xyp.unsmry) should already be part of your Project File.

In some cases, the auxiliary data are shown in a separate frame alongside the grid plot, as you saw with the Time/history Cell Plot in the preceding chapter. In other cases, the display is integrated into the grid plot.

19.1 Time/history WELL PLOTS

You've already used the time/history toggle to do the cell plot. Now you'll see another plot that can be placed in the same frame.



When the Time/history frame is active, the mouse pointer is in "probe" mode as indicated by the cross hairs. This time, instead of simply clicking on a cell, select the well selection crosshair option.



Then select the well at the producer. The best place to click is on the well symbol – the black circle at the top of

the well geometry. If needed, turn on the wells display using the toggle on the sidebar.

This time, the quick frame should display the plot from the XY file. It will be identical to the plot you would get using the XY Variables plot type. In fact, you control the variables that are plotted using that function, so if you don't see the variable(s) you want, simply switch to that plot type and make the desired selection.

19.2 BUBBLE PLOTS

Bubble plots also show data from the XY file, but instead of using a separate frame the values are shown right on the grid. This time, they are formatted as "bubbles" on the well head.

For this exercise, first turn off the Time/history plot to give you a better view of the main grid. Turn on the toggles for both Wells and Bubbles (note that you must have both grid and XY data loaded in order to turn on the Bubbles toggle). Click on the [...] button next to the Bubbles toggle to bring up this dialog, and change the settings to match these.

Once the settings are as shown, you can either hit **Apply** or turn on the Auto-Apply check box.

With the bubbles displayed, move the slider or press the Play button to animate the time steps. You'll see the bubbles change to reflect the values at each time step.

There are many additional options for displaying bubble plots. Refer to the User Manual for full instructions.

🎦 Pie Chart	—X —
V Show Bubbles	Auto-Apply Apply Changes
Type Variable Color Show in Pie	Use Multiplier
Prod WPR 🔻 Default 🔻 🔽	1
Prod OPR 🔻 Default 🔻 🔽	1
Prod GPR 🔻 Default 💌 📃	1
Prod WPR 🔻 Default 💌 🗖	1
Inj GIR 🔻 Default 💌 📃	1
Inj OIR 🔻 Default 💌 🗖	1
Inj WIR 🔻 Default 💌 🗖	1
Inj GOR 🔻 Default 💌 📃	1
Bubble Size	
Dynamic Range R	ing S <u>c</u> ale Diameter 💌
Static	🗧 Units Grid (%) 🔻
Labels	
Value Eont Helvetica Bold	▼ C <u>o</u> lor Gray ▼
Name Size 2	Uni <u>t</u> s Frame %
Delta Values	
Show Deltas Delta File Spe9a	
V Normalize Delta Max 100	
Bubble Style File	
Load	<u>S</u> ave
	Close Help

Click the save button to update your project file with the bubble styles. The next time you display bubbles with this project, you won't have to repeat the style selections.



19.3 STREAMLINES

Tecplot RS will display streamline data in 3D Plot views, providing a look at how fluids move through the reservoir model over time. In most cases, streamline data are stored separately from the grid file but they will be associated with it. For this exercise, you'll create a new project using grid and streamline files from the examples folder.

The first step is to create a new project, either by clicking on the button in the toolbar or by selecting **Project > New** from the menu. If you have an existing project open, you should generally elect to save your changes unless you've made specific alterations that you *don't* want to save.

The files for this exercise are found in a folder named "streamlines" that is a subfolder to "examples" where all other data have been located. The file is named exercise1_nk.grid. After browsing to and choosing that file, you'll see these options:

💟 Load G	Grid Dat	ta 💽
C:/Prog	jram F	iles/Tecplot/TecRS 20xx Rx/examples/streamlines/exercise1_nk.grid
V Make	<u>a</u> ctive	
Files	Optio	ons
<u>I</u> nit fil	le	C:/Program Files/Tecplot/TecRS 20xx Rx/examples/streamlines/exercise1_nk.init
<u>R</u> esta	art file	C:/Program Files/Tecplot/TecRS 20xx Rx/examples/streamlines/exercise1_nk.unrst
<u>X</u> Y file	e (C:/Program Files/Tecplot/TecRS 20xx Rx/examples/streamlines/exercise1_nk.unsmry
<u>D</u> isplay	name	exercise1_nk
<u>S</u> tream	lines	C:/Program Files/Tecplot/TecRS 20xx Rx/examples/streamlines/exercise 1_nk.slnspec
Sur <u>v</u> ey	wells	
		OK Cancel Help

When you select the grid file, the solution data should be filled in for you automatically. Note that there is a separate field for choosing the streamline file underneath the solution data file list. Since the streamline file had the same base name as the grid file, it was found automatically. The [...] browse button can be used to load streamlines that are named differently.

Once the data have been loaded you should select the 3D Grid plot type, if needed. Then, choose Streamlines in the Inside View type and set the options as shown here:

Times —					
			23	Jun	1985
-	🕨 🕨			ľ	(·····)
Inside Views					
Streamlines		•] 🔳	Show	
📃 Persisten	ıt			Ghost	
				Appl	у]
Select <u>b</u> y: <u>⊂</u> olor by: Property: Skjp:	All Pair SWAT 2	All			
<u>W</u> idth:	0.2 🗦				
		TOF:	3.8	5285e-	+008
		VL	og		

You will also need to advance the time slider at least one step past the first time (streams rarely exist at the first time step).

Chapter 19: Combo Plots



As with any RS plot, you have control over which data to show and how to display it. The display options are part of the Streamlines Inside View sidebar.

Note that after making changes you may need to click on the **Apply** button to update the plot.

Time Slider

Streamlines data are computed and recorded at different start times. These times are linked to the grid time slider. You can move the slider to a new position to see the stream simulation at that time, and you can even animate the progression. If stream times to not exactly match the grid times, the display will show the nearest stream *on or before* the selected grid time.

Select By

When this option is first launched, the Select By option defaults to "All", meaning all streamlines are flagged for display. You may change this in order to limit the streams that are viewed. You can choose the streams according to their Source (usually the injector well), Sink (a boundary or producer well), or by individual Pairs.

When you choose a new Select By option, the multi-select list to the right is cleared and repopulated with the available source, sink, or pair identifiers. You can then elect which ones to display by highlighting your choices in the list.

The example file contains a single source (the injector well), two sinks (the producer wells), and thus two pairs. Feel free to experiment with different selections.

Color By

Use this option to control how streams are colored. Your choices include:

- **Source:** The program will cycle through eight colors, using a different one for each source or injector well.
- **Sink:** Streamline color will be determined by the termination well or boundary.
- **Pair:** Each well pair will be plotted in a different color (cycling through the 8 available colors).
- Variable: The streams will be multi-colored, according to the variable values assigned to each stream node or segment. If multiple variables are included, you may choose which one from the Variable option menu. If you are using one of the supplied paper layout templates, a separate legend should appear for the streamline variable.
- **Time of Flight:** Streams may be colored according to the Time of Flight value associated with each node.

Skip

The Skip interval is used to reduce the number of streamlines displayed, and is especially helpful when there are so many streams that plotting all of them makes it impossible to see details. The skip factor defaults to 2 (plot every other stream), but you may select a value from 1 to 100. Regardless of the skip factor, the program always plots at least one stream between each selected well pair.

Time of Flight

This slider makes is possible to visualize the progress of streams over time. The slider is scaled over the full range of Time of Flight (TOF) values for the selected streams. If you position it at an intermediate point, partial streamlines are drawn according to that limit.

Use Log Scale

It is not unusual for a very small percentage of the streamlines to have a much longer TOF than the rest. This can skew the TOF range so that most of the progress occurs at the very bottom of the scale. In these cases, there is little difference in shading when coloring by Time of Flight, and you often lack enough fineness in the scale slider to control the display. This can be corrected using the Log Scale option, which will apply a logarithmic scale over the TOF range. This will impact both the color bands used when streams are colored by Time of Flight, and will make the scale bar usable for these cases.



CHAPTER 20: GRID COMPARISON PLOTS

In Chapter 9 you saw how you can create comparison XY plots using two or more files. This time you'll see how to do side-by-side comparisons of grid data.



You'll use a new set of files for this exercise, so start by choosing the New Project tool button or menu option.

The new files can be found in the Examples folder of your Tecplot RS installation under a sub-folder named **comparisons**. You'll need load three different grid files and their associated solution data files (.init and .unrst files). The files are in Eclipse/SLB format, and the file names are spe9a, spe9b, and spe9c. The solution files should be filled in automatically once you choose the grid file.

If you open the Manage Data dialog, you should see that you have three grids loaded with spe9a as the active data set.

💟 Manage D	ata		-×
Current Proje	ct File:		
<none></none>			
XY Grid	Templates	Macros	Unload
Active Data	Set:		
FILE NAME SOLUTION SOLUTION TIME STEP WELLS : 20 GLOBAL: I,J,K plar Total cell: Active ce	: spe9a.grid : spe9a.init : spe9a.unrst : spe : 50 6 nes : 24, 25, 15 : 9000 : s: 9000 : sr - 0		* III •
<u>D</u> isplay As	spe9a		pdate
Available G	rid Data <u>S</u> ets:		
spe9a C spe9b C spe9c C	:/Program Files/ :/Program Files/ :/Program Files/	Tecplot/Teo Tecplot/Teo Tecplot/Teo	RS 20xx RS 20xx RS 20xx I
•	III		F.
	0	ĸ	Help

Once all three files are loaded, choose the 3D Grid plot type and select the PRESSURE variable. Move the time slider all the way to the right to display the last time step:



Chapter 20: Grid Comparison Plots

Finally, at the bottom of the sidebar in the area marked "Data Set", turn on the Compare toggle.

Data Set	
Compare	Options
Show Deltas	
3D Grid	- ?

💟 Compare Grid Data
Compare
Active Data Set:
spe9a 🔻
Select files for Comparisons:
Active spe9a
spe90
Show Deltas
Close Help

A new dialog, Compare Grid Data, is displayed. When you asked RS to create a comparison plot, it selected the second file by default but it also automatically launched the Compare Grid options dialog so that you could change that selection if desired.

You can also launch this dialog by clicking on the **Options** button next to the Compare toggle.

💟 Compare Grid Data 🗾	<
🗹 Compare	
Active Data Set:	
spe9a.grid 🗸	
Select files for Comparisons:	
Active spe9a.grid]
spe9b.grid spe9c.grid	
E Shaw Dalkas	1
Close Help	

To compare all three files at once, highlight both spe9b and spe9c in the selection list.

Note that the active file is also included in the list and identified as such. Although it is possible to select it, this would result in comparing the file to itself, so you should normally leave it unselected.

However, there's also a separate control for choosing the active data set. This allows you to change the master data set to which all other grids are compared. When doing grid comparisons, it's best to use this dialog to choose the active data set (instead of the Manage Data dialog) since it is smarter about 'swapping' between other comparison grids.
Now all three grids are shown:



Although they look the same, you're actually viewing three different data sets. Selections you make on the sidebar will be applied to all. Try rotating the view or changing the variable, time step, or display toggles. You should see all three frames update accordingly.

The number of frames shown is controlled by the number of data sets being compared - the settings in the Multi-Frame dialog are not used here. Other settings in that dialog are also overridden; for example, turning on the Wells display will always show wells on all frames even if well linking is turned off.

The data sets shown here represent three separate simulator runs with slight variations in the input parameters. It's difficult to see the differences, since the values don't vary much. If we change the display to show the delta (difference) values instead, the differences will become clearer.

Start by choosing the SGAS variable, and then toggle on the Show Deltas toggle. This toggle is found on both the Compare Grid Data options dialog and on the sidebar. Your display will now show something like this, and it's much easier to see where differences exist. Your image may not match exactly since we've rotated and zoomed in a bit, but you can do the same.



Note that the first frame shows the raw values from the active data set. The other two frames show the delta values – the value from the active set minus the value for the same cell in the comparison data set, and the frame title reflects this. You'll also see that the legends on the smaller frames span a narrower range of values, both positive and negative, with 0 at the center. This makes the differences much easier to identify.

These sample data sets were all created from the same simulator. That isn't always the case in real life – you may wish to do comparisons for solutions from different simulators. In those situations the data may not align as well as these do. For example:

- The grid dimensions may not match or the coordinate system may be different.
- The simulators may use different names for the same value.
- The time steps may not span the same range or be on the exact same dates.

Tecplot RS handles these situations as follows:

- If the grid origins or coordinate units are different, the views won't be linked. You'll simply have to do rotations and zooms on each frame separately.
- If the grid IJK dimensions or number of cells is different, you won't be able to calculate delta values but you'll still be able to do side-by-side displays. 2D Grid plots and inside views that reference IJK planes will work up to the limits of the planes in each grid. For example, if you select K plane 18 in the active grid and the comparison grid has only 15 K layers, nothing will be shown in the comparison frame, but selecting K plane 12 will show data in both frames.
- If the variable names are different you can define aliases, just as you did for XY plots (see chapter 9 of this tutorial). After defining an alias for a variable that is already selected for display, you may need to switch to a different variable and then back again in order for the new alias to be recognized.
- If the times are not a match, Tecplot RS will find the date closest to the one selected. The frame title will reflect what was used.

In Conclusion

We hope you have found this tutorial to be helpful for getting started with Tecplot RS. You should now have a solid foundation for navigating the program and creating the various plots. There are many more features, including macros, pick blanking, history matching, cross plots, and templates, to name a few. Now that you are familiar with the basic operation, you should feel comfortable exploring these other options.

There are many additional resources for learning the program. Help buttons exist on almost all dialogs and from the top level menu. The User's Manual provides detail on all options. Our online Knowledge Base has answers for many frequently asked questions, and the Tecplot Talk user forum lets you communicate with other users of the product. Finally, customers with an active TecPLUS subscription may contact support for assistance (support@tecplot.com).

Thank you for choosing Tecplot RS!